Kaze Protective Respirator

Original

Certificate and test reports

Directory

Nelson Labs – N95 test reports	Page 2-6
SGS REACH test reports	Page 7-41
SGS Microbial Cleanliness test report	Page 42-43
BSI – CE Module B & C2 (for COVID-19)	Page 44-49
EU Declaration of Conformity (for COVID-19)	Page 50
BSI - CE Module B & C2 (for EN149:2001+A1:2009)	Page 51-56
EU Declaration of Conformity (for EN149:2001+A1:20	009) Page 57
BSI - EN 149:2001+A1:2009 test reports	Page 58-81
CNAS - EN149 full test report	Page 82-93
Intertek - Kaze BFE test report	Page 94-97
Kaze KN95 test reports	Page 98-146
Kaze Protective Respirator - MSDS	Page 147-152



Sponsor:
Michael Wong
Huizhou Bowen Manufacturing Ltd.
Xinnan 1st Road, Xianan Village,
Yuanzhou Town, Boluo County
Huizhou City, Guangdong,
CHINA

Sodium Chloride (NaCl) Aerosol Test Final Report

Test Article: KAZE Protective Respirator

Study Number: 1306452-S01 Study Received Date: 03 Jun 2020

Testing Facility: Nelson Laboratories, LLC

6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0014 Rev 09

Deviation(s): None

Summary: This procedure was performed to evaluate particulate filter penetration as specified in 42 CFR Part 84 and TEB-APR-STP-0059 for requirements on a N95 respirator. Respirators were conditioned then tested for particle penetration against a polydispersed, sodium chloride (NaCl) particulate aerosol. The challenge aerosol was dried, neutralized, and passed through the test article at a concentration not exceeding 200 mg/m³. The initial airflow resistance and particle penetration for each respirator was determined.

According to 42 CFR Part 84.64, pretesting must be performed by all applicants as part of the application process with NIOSH. Results seen below are part of that pretesting and must be submitted to and accepted by NIOSH for respirator approval.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.





Robert Dieker electronically approved for

Study Director

Curtis Gerow

17 Jul 2020 17:58 (+00:00)

Study Completion Date and Time

801-290-7500

nelsonlabs.com

sales@nelsonlabs.com

brd

FRT0014-0002 Rev 6 Page 1 of 3



The NIOSH N95 filter efficiency as stated in 42 CFR Part 84.181 is a minimum efficiency for Results: each filter of ≥95% (≤5% penetration). The test articles submitted by the sponsor conform to the NIOSH N95 criteria for filter efficiency.

THE CHILDREN TO THE CHILDREN			
Test Article Number	Corrected ^a Initial Airflow Resistance (mm H ₂ O)	Maximum Particle Penetration (%)	Filtration Efficiency (%)
1	14.5	0.790	99.210
2	15.0	1.00	99.00
3	15.7	0.825	99.175
4	15.8	0.888	99.112
5	15.4	0.775	99.225
6	15.4	0.461	99.539
7	16.0	0.724	99.276
8	15.8	1.03	98.97
9	17.7	0.936	99.064
10	17.7	0.868	99.132
11	17.6	0.677	99.323
12	18.7	0.935	99.065
13	16.8	0.628	99.372
14	16.0	0.719	99.281
15	16.0	0.629	99.371
16	14.7	1.14	98.86
17	16.1	0.742	99.258
18	15.9	0.761	99.239
19	14.8	0.701	99.299
20	14.9	0.887	99.113
a			

^a The final airflow resistance value for each test article was determined by subtracting out the background resistance from the system.

Test Method Acceptance Criteria: The filter tester must pass the "Tester Set Up" procedure. The airflow resistance and particle penetration of the reference material must be within the limits set by the manufacturer.

Filter Test Procedure: Prior to testing, respirators were taken out of their packaging and placed in an environment of $85 \pm 5\%$ relative humidity (RH) and 38 ± 2.5 °C for 25 ± 1 hours.



The filter tester used in testing was a TSI® CERTITEST® Model 8130 Automated Filter Tester that is capable of efficiency measurements of up to 99.999%. It produces a particle size distribution with a count median diameter of 0.075 ± 0.020 microns (µm) and a geometric standard deviation not exceeding 1.86 µm. The mass median diameter was approximately 0.26 µm, which is generally accepted as the most penetrating aerosol size. The reservoir was filled with a 2% NaCl solution and the instrument allowed a minimum warm-up time of 30 minutes. The main regulator pressure was set to 75 \pm 5 pounds per square inch (psi). The filter holder regulator pressure was set to approximately 35 psi. The NaCl aerosol generator pressure was set to approximately 30 psi and the make-up airflow rate was set to approximately 70 liters per minute (L/min).

The NaCl concentration of the test aerosol was determined in mg/m³ by a gravimetric method prior to the load test assessment. An entire respirator was mounted on a test fixture, placed into the filter holder, and the NaCl aerosol passed through the outside surface of the test article at a continuous airflow rate of 85 ± 4 L/min. In accordance with NIOSH policy, three respirators were challenged until 200 ± 5 mg of NaCl had contacted each test article. Based upon the load pattern of NIOSH Type 1, the initial penetration reading of the remaining 17 respirators was recorded.





Sponsor: Michael Wong Huizhou Bowen Manufacturing Ltd. Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County Huizhou City, Guangdong Province,

Determination of Inhalation and Exhalation Resistance for Air-Purifying Respirators Final Report

Test Article: KAZE Protective Respirator

Study Number: 1306453-S01 Study Received Date: 03 Jun 2020

> Testing Facility: Nelson Laboratories, LLC

> > 6280 S. Redwood Rd.

Salt Lake City, UT 84123 U.S.A.

Test Procedure(s): Standard Test Protocol (STP) Number: STP0145 Rev 05

Deviation(s): None

This procedure was performed to evaluate the differential pressure of non-powered airpurifying particulate respirators in accordance with 42 CFR Part 84.180. The air exchange differential or breathability of respirators was measured for inhalation resistance using NIOSH procedure TEB-APR-STP-0007 and exhalation resistance with NIOSH procedure TEB-APR-STP-0003. The differential pressure technique is a simple application of a basic physical principle employing a water manometer differential upstream and downstream of the test material, at a constant flow rate.

According to 42 CFR Part 84.64, pretesting must be performed by all applicants as part of the application process with NIOSH. Results seen below are part of that pretesting and must be submitted to and accepted by NIOSH for respirator approval.

The inhalation resistance criteria as stated in 42 CFR Part 84.180 is an initial inhalation not exceeding 35 mm water column height pressure. The test articles submitted by the sponsor conform to this NIOSH criterion for airflow resistance.

The exhalation resistance criteria as stated in 42 CFR Part 84.180 is an initial exhalation not exceeding 25 mm water column height pressure. The test articles submitted by the sponsor conform to this NIOSH criterion for airflow resistance.

All test method acceptance criteria were met. Testing was performed in compliance with US FDA good manufacturing practice (GMP) regulations 21 CFR Parts 210, 211 and 820.





Sean Shepherd electronically approved for

Study Director

Curtis Gerow

30 Jun 2020 18:54 (+00:00) Study Completion Date and Time

801-290-7500 nelsonlabs.com sales@nelsonlabs.com FRT0145-0001 Rev 3



Results:

Test Article Number	Inhalation Resistance (mm H ₂ O)	Exhalation Resistance (mm H ₂ O)
1	11.5	10.2
2	10.3	10.3
3	10.3	10.3

Test Method Acceptance Criteria: The resistance measurement for the reference plate must be within ±3 standard deviations of the mean established in the control chart.

Procedure: A complete respirator was mounted to a test fixture comprised of a metal plate with an approximate 3.5 inch diameter hole in the center to allow airflow to reach the mask. The sample holder was assembled by placing a Plexiglas collar around the test fixture and topping with another metal disc with a 3.5 inch opening in the center. The sample holder is held tightly together with clamps and connected to an air source. The manometer is attached to the sample holder by a connection port on the Plexiglas collar.

Before testing, the manometer was zeroed and the back pressure in the sample holder checked and verified to be acceptable. Resistance measurements were taken with a manometer capable of measuring at least 6 inches of water. For inhalation testing, a negative airflow (vacuum) was applied. For exhalation testing, a positive airflow (compressed air) was used. Airflow was passed through the sample holder at approximately 85 ± 2 liters per minute (L/min).



SL92109241840201TX

Date:March 08,2021

Page 1 of 22

HUIZHOU BOWEN MANUFACTURING LIMITED

XINNAN 1ST ROAD, XIANAN VILLAGE, YUANZHOU TOWN, BOLUO COUNTY, HUIZHOU CITY GUANGDONG PROVINCE, P.R. CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description COLOR NON-WOVEN FABRIC 16%; MELT BLOWN FABRIC 22%; HOT AIR

COTTON 12%; SKIN FRIENDLY NON-WOVEN FABRIC 10%; EAR THREAD

25%, NOSE CLIP 15%

PROTECTIVE RESPIRATOR IN

(A)ROYAL BLUE (B)FOREST PINE (C)POWER BLUE (D)CITRUS ORANGE (E)SWEET PEA (F)ULTRA-VIOLET (G)SANDÝ BEIGE (H)MAROON (I)FUCHSIA (J)RACING RED (K)ROSE QUARTZ

(L)DOVE GREY (M)ESPRESSO (N)SILVER GREY

(P)LIGHT BLUSH (Q)NATURAL SAND

(O)CHAMPAGNE

(R)WHITE

(A)royal blue; (B)forest pine; (C)power blue; (D)citrus orange; (E)sweet pea;

(F)ultra-violet; (G)sandy beige; (H)maroon; (I)fuchsia; (J)racing red; (K)rose Sample Color

quartz; (L)dove grey; (M)espresso; (N)silver grey; (O)champagne; (P)light blush;

(Q)natural sand; (R)white

COLOR NON-WOVEN FABRIC 16%; MELT BLOWN FABRIC 22%; HOT AIR COTTON 12%; SKIN FRIENDLY NON-WOVEN FABRIC 10%; EAR THREAD

25%, NOSE CLIP 15%

KAZE-05 Style No.

Composition

HUIZHOU BOWEN MANUFACTURING LIMITED Manufacturer

Country of Destination United States, Europe

Sample Receiving Date Mar 02, 2021

Testing Period Mar 02, 2021 - Mar 08, 2021

Test Result(s) Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Selected test(s) as requested by applicant **Test Performed**





Test Report SL92109	9241840201TX	Da	te:March 08,202	1	Page 2 of 22
Conclusion	Α	В	С	D	Remark
Pentachlorophenol (PCP)	PASS	PASS	PASS	PASS	
Azo Dyes	PASS	PASS	PASS	PASS	
Total Cadmium (Cd)	PASS	-	_	-	
Nonylphenol Ethoxylates(NPEOs)	PASS	PASS	PASS	PASS	
Organotin Compounds	PASS	PASS	PASS	PASS	
Polycyclic Aromatic Hydrocarbons (PAHs)	PASS	<u>-</u>	-	-	
Short Chain Chlorinated Paraffins (SCCP)	PASS	/ -	- 1	/ -	
Phthalates	PASS	-	- ' /	-	
Conclusion	E	F	G	н	Remark
Pentachlorophenol (PCP)	PASS	PASS	PASS	PASS	
Azo Dyes	PASS	PASS	PASS	PASS	•
Nonylphenol Ethoxylates(NPEOs)	PASS	PASS	PASS	PASS	
Organotin Compounds	PASS	PASS	PASS	PASS	
Conclusion	1	J	K	L	Remark
Pentachlorophenol (PCP)	PASS	PASS	PASS	PASS	4
Azo Dyes	PASS	PASS	PASS	PASS	
Nonylphenol Ethoxylates(NPEOs)	PASS	PASS	PASS	PASS	
Organotin Compounds	PASS	PASS	PASS	PASS	
Conclusion	M	N	0	Р	Remark
Pentachlorophenol (PCP)	PASS	PASS	PASS	PASS	· ·
Azo Dyes	PASS	PASS	PASS	PASS	
Nonylphenol Ethoxylates(NPEOs)	PASS	PASS	PASS	PASS	
Organotin Compounds	PASS	PASS	PASS	PASS	
Conclusion	Q	R	Remark		
Pentachlorophenol (PCP)	PASS	PASS			
Azo Dyes	PASS	-			
Nonylphenol Ethoxylates(NPEOs)	PASS	PASS			. []
Organotin Compounds	PASS	PASS			

Remark(s): PASS=Meet Client's Requirement

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Lily Wang (Account Manager)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits or Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document not be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

of email: CN.Decreeck@sia.com 198 Rezin Road, Scentsch Park (Garaghou Economic/Sechnology Development Dishict (Garaghou China 510663 t (86–20),82155555 t (86–20),82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86–20),82155555 t (86–20),82075169 e sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 3 of 22

COMPONENT LIST / List of Materials

Sample	Component	5		0.1	5
No.	No.	Description	Material	Color	Remark
Α	1	Flat band	Synthetic Fibers	Royal blue	
Α	2	Outer non-woven fabric with logo	Synthetic Fibers	Royal blue	
D	3	Flat band	Synthetic Fibers	Citrus orange	
D	4	Outer non-woven fabric with logo	Synthetic Fibers	Citrus orange	
					BR material
Α	5	Inner layer non-woven fabric	Synthetic Fibers	White	type same as
					A
					BR material
Α	6	Hot air cotton	Blended Fibers	White	type same as
				"	Α
					BR material
Α	7	Melt-blown material	Synthetic Fibers	White	type same as
		*	Y		Α
_	_				BR material
Α	8	Foam with adhesive backing	Foam	Dark grey	type same as
					Α
			.		BR material
Α	9	Nose clip	Plastics	White	type same as
	4				A
Δ.	10	A Produktion of	DI C	140.30	BR material
Α	10	Adjustable beads	Plastics	White	type same as
	11	Flat band	Cynathatia Fibaya	Faract nine	Α
В	11		Synthetic Fibers	Forest pine	
B C	12 13	Outer non-woven fabric with logo Flat band	Synthetic Fibers	Forest pine	
C	14	Outer non-woven fabric with logo	Synthetic Fibers Synthetic Fibers	Power blue Power blue	· ·
E	15	Flat band	Synthetic Fibers		
E	16	Outer non-woven fabric with logo	Synthetic Fibers	Sweet pea Sweet pea	
F	17	Flat band	Synthetic Fibers	Ultra-violet	
F	18	Outer non-woven fabric with logo	Synthetic Fibers	Ultra-violet	
G	19	Flat band	Synthetic Fibers	Sandy beige	
G	20	Outer non-woven fabric with logo	Synthetic Fibers	Sandy beige	
H	21	Flat band	Synthetic Fibers	Maroon	
H	22	Outer non-woven fabric with logo	Synthetic Fibers	Maroon	
11	23	Flat band	Synthetic Fibers	Fuchsia	
i	24	Outer non-woven fabric with logo	Synthetic Fibers	Fuchsia	
J	25	Flat band	Synthetic Fibers	Racing red	-
J	26	Outer non-woven fabric with logo	Synthetic Fibers	Racing red	
K	27	Flat band	Synthetic Fibers	Rose quartz	
K	28	Outer non-woven fabric with logo	Synthetic Fibers	Rose quartz	
L	29	Flat band	Synthetic Fibers	Dove grey	
L	30	Outer non-woven fabric with logo	Synthetic Fibers	Dove grey	4
M	31	Flat band	Synthetic Fibers	Espresso	
M	32	Outer non-woven fabric with logo	Synthetic Fibers	Espresso	
N	33	Flat band	Synthetic Fibers	Silver grey	
N .	34	Outer non-woven fabric with logo	Synthetic Fibers	Silver grey	
0	35	Flat band	Synthetic Fibers	Champagne	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents with http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Occument.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits (Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to retransaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omail: CN. Descheck @ sus.com 188 Ratu Road Scarlach Par Guarghou Economics Rethnology Development Disht (Guarghou China 510663 t (86–20) 82155555 f (86–20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学域科珠路198号 邮编: 510663 t (86–20) 82155555 f (86–20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 4 of 22

COMPONENT LIST / List of Materials

Sample No.	Component No.	Description	Material	Color	Remark
0	36	Outer non-woven fabric with logo	Synthetic Fibers	Champagne	
Р	37	Flat band	Synthetic Fibers	Light blush	
Р	38	Outer non-woven fabric with logo	Synthetic Fibers	Light blush	
Q	39	Flat band	Synthetic Fibers	Natural sand	
Q	40	Outer non-woven fabric with logo	Synthetic Fibers	Natural sand	
R	41	Flat band	Synthetic Fibers	White	
R	42	Outer non-woven fabric with logo	Synthetic Fibers	White	

Inspection & Testing Services 4

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sas.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sas.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's solic responsibility is to its Client and the document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) tested and s

or omaif: CN.Doccheck@sus.com |198/acturRoad,Scientich Park (usarghouEconnickTechnology Development Dishict, Guarghou,China 510663 1 (86–20) 82155555 1 (86–20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 1 (86–20) 82155555 1 (86–20) 82075169 a sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 5 of 22

Test Result

European Regulation POPs (EU) 2019/1021 - Pentachlorophenol (PCP)

Test Method: Modified § 64 LFGB, BVL, B 82.02.8-2001 Alkaline (KOH) digestion, analysis was performed by GC-ECD or GC-MS.

Test Item(s) Pentachlorophenol (PCP) Comment	<u>CAS_NO</u> 87-86-5	<u>Unit</u> mg/kg	MDL 1+3+11 13+15+17 19+21+23 0.15 ND ND ND PASS PASS PASS
Test Item(s) Pentachlorophenol (PCP) Comment	<u>CAS NO</u> 87-86-5	<u>Unit</u> mg/kg	MDL25+27+29 31+33+35 2+4+12 0.15 ND ND ND PASS PASS PASS
Test Item(s) Pentachlorophenol (PCP) Comment	<u>CAS NO</u> 87-86-5	<u>Unit</u> mg/kg	MDL14+16+18 20+22+24 26+28+30 0.15 ND ND ND PASS PASS PASS
Test Item(s) Pentachlorophenol (PCP) Comment	<u>CAS_NO</u> 87-86-5	<u>Unit</u> mg/kg	MDL37+39+41 38+40+42 5+6+7 0.15 ND ND ND PASS PASS PASS
Test Item(s) Pentachlorophenol (PCP) Comment	<u>CAS_NO</u> 87-86-5	<u>Unit</u> mg/kg	MDL <u>32+34+36</u> 0.15 ND PASS

Notes:

RL (Reporting limit): 0.15 mg/kg

ND = Not Detected(< RL)

Requirement: Banned(< 0.5 mg/kg)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-



SL92109241840201TX

Date: March 08,2021

Page 6 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Direct reduction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	<u>1+3+11</u> ND	<u>13+15+17</u> ND	<u>19+21+23</u> ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine /	615-05-4	mg/kg	5	ND	ND	ND
2,4-Diaminoanisole 4,4'-diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine /	95-80-7	mg/kg	5	ND	ND	ND
2,4-Toluylendiamine, TDA 2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment		1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content apprearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omail: CN.Doscheck@sps.com |198/earb(Rod)Scarlack)Per(GuarghouEconnicATechnology Development Dishic(Guarghou,China 510663 t (86-20) 82155555 f (86-20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 7 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Direct reduction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	<u>25+27+29</u> ND	31+33+38 ND	5 <u>2+4+12</u> ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine / 2,4-Diaminoanisole	615-05-4	mg/kg	5	ND	ND	ND
4,4' -diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'-diaminodiphenylmethane	838-88-0	mg/kg	5	ND	ND	ND
p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine / 2,4-Toluylendiamine, TDA	95-80-7	mg/kg	5	ND	ND	ND
2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment		1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a



SL92109241840201TX

Date:March 08,2021

Page 8 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Direct reduction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	<u>14+16+18</u> ND	20+22+24 ND	26+28+30 ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine / 2,4-Diaminoanisole	615-05-4	mg/kg	5	ND	ND	ND
4,4' -diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine / 2,4-Toluylendiamine, TDA	95-80-7	mg/kg	5	ND	ND	ND
2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment	,	1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a

or omail: CN.Doscheck@sps.com |198/earb(Rod)Scarlack)Per(GuarghouEconnicATechnology Development Dishic(Guarghou,China 510663 t (86-20) 82155555 f (86-20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date: March 08,2021

Page 9 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Direct reduction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	37+39 ND	<u>38+40</u> ND	32+34+36 ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine / 2,4-Diaminoanisole	615-05-4	mg/kg	5	ND	ND	ND
4,4' -diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4	838-88-0	mg/kg	5	ND	ND	ND
p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine / 2,4-Toluylendiamine, TDA	95-80-7	mg/kg	5	ND	ND	ND
2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment	7	1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content apprearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omail: CN.Doscheck@sps.com |198/earb(Rod)Scarlack)Per(GuarghouEconnicATechnology Development Dishic(Guarghou,China 510663 t (86-20) 82155555 f (86-20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 10 of 22

Notes:

RL (Reporting limit): 5 mg/kg (for individual compound)

ND = Not Detected(< RL)

Requirement: 30 mg/kg (for individual compound)

(1)Method A is direct reduction, direct reduction refers to the extraction and reduction according to ISO 14362-1:2017 clause 10.2 and relevant clauses. Method B is colorant extraction, colorant extraction refers to the colourant extraction and subsequent reduction according to ISO 14362-1:2017 clause 10.1 and relevant clauses.

(2)The ISO 14362-1:2017 methods will enable further cleavage of 4 aminoazobenzene to non forbidden amines: aniline and 1,4 phenylenediamine, therefore, the test method of ISO 14362-3:2017 was employed to verify the presence of 4 aminoazobenzene

(3) Max. limit specified by entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 (previously restricted under Directive 2002/61/EC).

(4)Whenever 4-aminodiphenyl (CAS number 92-67-1), 2-naphylamine (CAS number 91-59-8) and 4-methoxy-m-phenylene-diamine (CAS number 615-05-4) is found, the use of banned azo colorants cannot be reliably ascertained without additional information, e.g. the chemical structure of the colorants used. In case polyurethane materials are used, e.g. PU foams and coatings and in prints, it cannot be ruled out that certain amines, e.g. 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) and 2,4-toluylen-diamine(TDA, CAS number 95-80-7) are released from the PU component and not from a banned azo colorant.

In case of pigment prints care has to be taken that 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) is not released from a source of banned azo colorants but from e.g. a chemical fixing agent.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.gsp.x.nd, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions-en-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omaif: CN. Descheck@sus.com 198 Kadu Road, Swintch Park Guarghou EconomicAll Echnology Development District, Guarghou, China 510663 t (86–20) 82155555 t (86–20) 82075169 www.sgsgroup.com.cn 中国 · 广州 · 经济技术开发区科学城科珠路198号 邮编: 510663 t (86–20) 82155555 t (86–20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date: March 08,2021

Page 11 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Colorant extraction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	<u>1+3+11</u> ND	<u>13+15+17</u> ND	<u>19+21+23</u> ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine /	615-05-4	mg/kg	5	ND	ND	ND
2,4-Diaminoanisole 4,4'-diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine /	95-80-7	mg/kg	5	ND	ND	ND
2,4-Toluylendiamine, TDA 2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment		1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a



SL92109241840201TX

Date: March 08,2021

Page 12 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Colorant extraction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	CAS_NO 92-67-1	<u>Unit</u> mg/kg	MDL 5	25+27+29 ND	31+33+35 ND	5 <u>2+4+12</u> ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine / 2,4-Diaminoanisole	615-05-4	mg/kg	5	ND	ND	ND
4,4' -diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine /	95-80-7	mg/kg	5	ND	ND	ND
2,4-Toluylendiamine, TDA 2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment		1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content apprearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omail: CN.Doscheck@sps.com |198/earb(Rod)Scarlack)Per(GuarghouEconnicATechnology Development Dishic(Guarghou,China 510663 t (86-20) 82155555 f (86-20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date: March 08,2021

Page 13 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Colorant extraction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	<u>14+16+18</u> ND	20+22+24 ND	26+28+30 ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine / 2,4-Diaminoanisole	615-05-4	mg/kg	5	ND	ND	ND
4,4' -diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine / 2,4-Toluylendiamine, TDA	95-80-7	mg/kg	5	ND	ND	ND
2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment	,	1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document not be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date: March 08,2021

Page 14 of 22

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Colorant extraction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

<u>Test Item(s)</u> 4-Aminobiphenyl	<u>CAS_NO</u> 92-67-1	<u>Unit</u> mg/kg	MDL 5	37+39 ND	<u>38+40</u> ND	32+34+36 ND
Benzidine	92-87-5	mg/kg	5	ND	ND	ND
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotoluene	99-55-8	mg/kg	5	ND	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND	ND
4-methoxy-m-phenylenediamine /	615-05-4	mg/kg	5	ND	ND	ND
2,4-Diaminoanisole 4,4'-diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND	ND
3,3' -dichlorobenzidine	91-94-1	mg/kg	5	ND	ND	ND
3,3' -dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND	ND
3,3' -dimethylbenzidine	119-93-7	mg/kg	5	ND	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dimethyl-4,4'	838-88-0	mg/kg	5	ND	ND	ND
-diaminodiphenylmethane p-cresidine	120-71-8	mg/kg	5	ND	ND	ND
4,4' -methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND	ND
4,4' -oxydianiline	101-80-4	mg/kg	5	ND	ND	ND
4,4' -thiodianiline	139-65-1	mg/kg	5	ND	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND	ND
4-methyl-m-phenylenediamine /	95-80-7	mg/kg	5	ND	ND	ND
2,4-Toluylendiamine, TDA 2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND	ND
Comment		1		PASS	PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content apprearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or omail: CN.Doscheck@sps.com |198/earb(Rod)Scarlack)Per(GuarghouEconnicATechnology Development Dishic(Guarghou,China 510663 t (86-20) 82155555 f (86-20) 82075169 www.sgsgroup.com.cn 中国 - 广州 - 经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075169 e sgs.china@sgs.com



SL92109241840201TX

Date:March 08,2021

Page 15 of 22

Notes:

RL (Reporting limit): 5 mg/kg (for individual compound)

ND = Not Detected(< RL)

Requirement: 30 mg/kg (for individual compound)

(1)Method A is direct reduction, direct reduction refers to the extraction and reduction according to ISO 14362-1:2017 clause 10.2 and relevant clauses. Method B is colorant extraction, colorant extraction refers to the colourant extraction and subsequent reduction according to ISO 14362-1:2017 clause 10.1 and relevant clauses.

(2)The ISO 14362-1:2017 methods will enable further cleavage of 4 aminoazobenzene to non forbidden amines: aniline and 1,4 phenylenediamine, therefore, the test method of ISO 14362-3:2017 was employed to verify the presence of 4 aminoazobenzene

(3) Max. limit specified by entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 (previously restricted under Directive 2002/61/EC).

(4)Whenever 4-aminodiphenyl (ČAS number 92-67-1), 2-naphylamine (CAS number 91-59-8) and 4-methoxy-m-phenylene-diamine (CAS number 615-05-4) is found, the use of banned azo colorants cannot be reliably ascertained without additional information, e.g. the chemical structure of the colorants used. In case polyurethane materials are used, e.g. PU foams and coatings and in prints, it cannot be ruled out that certain amines, e.g. 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) and 2,4-toluylen-diamine(TDA, CAS number 95-80-7) are released from the PU component and not from a banned azo colorant.

In case of pigment prints care has to be taken that 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) is not released from a source of banned azo colorants but from e.g. a chemical fixing agent.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest event of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date: March 08,2021

Page 16 of 22

Entry 23 of Commission Regulation (EU) No 835/2012, (EU) No 494/2011 and (EU) 2016/217 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Cadmium(Cd)

Test Method: With reference to EN 1122: 2001, Method B, analysis was performed by AAS.

Test Item(s)
Cadmium (Cd)
Comment

<u>Unit</u> mg/kg MDL 8+9+10 5 **ND**

ND PASS

Notes:

RL (Reporting limit): 5 mg/kg ND = Not Detected(< RL) Requirement: 100 mg/kg

Entry 46a of Commission Regulation (EU) 2016/26 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Nonylphenol Ethoxylates(NPEOs)

Test Method: With reference to ISO 18254-1:2016, analysis was performed by LC-MS

Test Item(s)	Unit	MDL	1+3+11	13+15+17	⁷ 19+21+23	
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND	ND	ND	
Comment	0 0		PASS	PASS	PASS	
Test Item(s)	<u>Unit</u>	MDL	<u>25+27+29</u>	31+33+3	<u>85 2+4+12</u>	
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND	ND	ND	
Comment			PASS	PASS	PASS	
Test Item(s)	<u>Unit</u>	MDL	14+16+18	20+22+2	<u>24 26+28+30</u>	0
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND	ND	ND	_
Comment	0 0		PASS	PASS	PASS	
T - 1 H ()	11.9	MDI	07.00.44	00.40.4	10.5.0.7	
Test Item(s)	<u>Unit</u>	MDL	<u>37+39+41</u>			. (
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND	ND	ND	
Comment			PASS	PASS	PASS	
T 111 //)		, Apr	00.04.00			
Test Item(s)	<u>Unit</u>	MDL	<u>32+34+36</u>			
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND			
Comment			PASS			

Notes:

RL (Reporting limit) :30 mg/kg ND = Not Detected(< RL) Requirement: 100 mg/kg



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits or Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document not be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date: March 08,2021

Page 17 of 22

Entry 20 of Regulation (EC) No 276/2010 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Organotin Compounds

Test Method: SGS In-house method (GZTC CHEM-TOP-031, with reference to ISO 17353:2004), analysis was performed by GC-MS.

Test Item(s) Dibutyl tin (DBT) by weight of Tin Dioctyl tin (DOT) by weight of Tin Tributyl tin (TBT) by weight of Tin Triphenyl tin (TPhT) by weight of Tin Tricyclohexyltin (TCyT) by weight of Tin Trioctyltin (TOT) by weight of Tin Tripropyltin (TPT) by weight of Tin Trimethyltin(TMT) by weight of Tin Σ of Tri substituted organotin compounds calculated as tin Comment	Unit MDL mg/kg 100 mg/kg 100.00 mg/kg 100.00 mg/kg 100.00 mg/kg 100.00 mg/kg 100 mg/kg 100.00 mg/kg 100.00 mg/kg 100.00 mg/kg 100.00	ND ND ND ND ND ND ND	13+15+17 ND	ND N
$\frac{\text{Test Item(s)}}{\text{Dibutyl tin (DBT) by weight of Tin}}$ $\frac{\text{Dioctyl tin (DOT) by weight of Tin}}{\text{Dioctyl tin (TBT) by weight of Tin}}$ $\frac{\text{Tributyl tin (TBT) by weight of Tin}}{\text{Triphenyl tin (TPhT) by weight of Tin}}$ $\frac{\text{Tricyclohexyltin (TCyT) by weight of Tin}}{\text{Tripropyltin (TPT) by weight of Tin}}$ $\frac{\text{Trimethyltin(TMT) by weight of Tin}}{\text{Trimethyltin(TMT) by weight of Tin}}$ $\frac{\text{Diocharce}}{\text{Diocharce}}$	Unit MDL mg/kg 100 mg/kg 100.00	ND ND ND ND	ND ND ND ND ND ND ND ND ND ND ND ND	25 2+4+12 ND ND ND ND ND ND ND ND ND ND
$\frac{Test \ Item(s)}{Dibutyl \ tin \ (DBT)} \ by \ weight \ of \ Tin \\ Dioctyl \ tin \ (DOT) \ by \ weight \ of \ Tin \\ Tributyl \ tin \ (TBT) \ by \ weight \ of \ Tin \\ Triphenyl \ tin \ (TPhT) \ by \ weight \ of \ Tin \\ Tricyclohexyltin \ (TCyT) \ by \ weight \ of \ Tin \\ Tripropyltin \ (TOT) \ by \ weight \ of \ Tin \\ Tripropyltin \ (TPT) \ by \ weight \ of \ Tin \\ Trimethyltin \ (TMT) \ by \ weight \ of \ Tin \\ \Sigma \ of \ Tri \ substituted \ organotin \ compounds \ calculated \ as \ tin \\ \textbf{Comment}$	Unit MDL mg/kg 100 mg/kg 100.00 mg/kg 100.00	ND ND ND ND ND ND ND	ND ND ND ND ND ND ND ND ND ND ND ND	24 26+28+30 ND ND ND ND ND ND ND ND ND ND

Notes:

RL (Reporting limit): 100 mg/kg (for individual compound)

ND = Not Detected (< RL)

Requirement:

Tri substituted Organotin compound (TBT,TPhT,TCyT,TPT,TOT,TMT): 1000 mg/kg by weight of tin

(sum)

DBT: 1000 mg/kg by weight of tin DOT: 1000 mg/kg by weight of tin



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed varieties, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.agps, and, for electronic format documents, at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.agpx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is divised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the faw. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date: March 08,2021

Page 18 of 22

Entry 20 of Regulation (EC) No 276/2010 amending Annex XVII of REACH Regulation (EC) No 1907/2006 -**Organotin Compounds**

Test Method: SGS In-house method (GZTC CHEM-TOP-031, with reference to ISO 17353:2004), analysis was performed by GC-MS.

mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg	100 100 100.00 100.00 100.00 100.00 100 1	ND ND ND ND ND ND ND ND ND PASS	ND ND ND ND ND ND ND ND ND ND ND ND ND N	ND ND ND ND ND ND ND ND ND ND ND
Unit mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg	MDL 100 100.00 100.00 100.00 100.00 100.00	8+9+10 ND ND ND ND ND ND ND ND	32+34+36 ND ND ND ND ND ND ND	
	mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg mg/kg	mg/kg 100 mg/kg 100.00 mg/kg 100 mg/kg 100.00	mg/kg 100 ND mg/kg 100.00 ND mg/kg 100 ND mg/kg 100.00 ND	mg/kg 100 ND ND mg/kg 100 ND ND mg/kg 100.00 ND ND mg/kg 100.00 ND ND mg/kg 100.00 ND ND mg/kg 100 ND ND mg/kg 100 ND ND mg/kg 100 ND ND pass pass pass Unit MDL 8+9+10 32+34+36 mg/kg 100 ND ND mg/kg 100 ND ND mg/kg 100 ND ND mg/kg 100.00 ND ND mg/kg 100.00 ND ND mg/kg 100.00 ND ND mg/kg 100.00 ND ND mg/kg 100 ND ND mg/kg 100.00 ND ND mg/kg 100 ND

Notes:

Comment

RL (Reporting limit): 100 mg/kg (for individual compound)

ND = Not Detected (< RL)

Requirement:

Tri substituted Organotin compound (TBT,TPhT,TCyT,TPT,TOT,TMT): 1000 mg/kg by weight of tin

PASS

PASS

(sum)

DBT: 1000 mg/kg by weight of tin DOT: 1000 mg/kg by weight of tin





SL92109241840201TX

Date: March 08,2021

Page 19 of 22

Entry 50 of Commission Regulation (EU) No 1272/2013 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Polycyclic Aromatic Hydrocarbons(PAHs)

Test Method: With reference to AfPS GS 2019:01 PAK, analysis was performed by GC-MS.

Test Item(s)	CAS NO	Unit	MDL	8+10
Benzo(a)anthracene(BaA)	56-55-3	mg/kg	0.1	ND
Chrysene(CHR)	218-01-9	mg/kg	0.1	ND
Benzo(b)fluoranthene(BbF)	205-99-2	mg/kg	0.1	ND
Benzo(j)fluoranthene(BjF)	205-82-3	mg/kg	0.1	ND
Benzo(k)fluoranthene(BkF)	207-08-9	mg/kg	0.1	ND
Benzo(a)pyrene(BaP)	50-32-8	mg/kg	0.1	ND
Benzo(e)pyrene(BeP)	192-97-2	mg/kg	0.1	ND
Dibenzo(a,h)anthracene(DBA)	53-70-3	mg/kg	0.1	ND
Comment				PASS

Notes:

RL (Reporting limit): 0.1 mg/kg (each)

ND = Not Detected(< RL)
Requirement: 1 mg/kg (each)

European Regulation POPs (EU) 2019/1021 - Short Chain Chlorinated Paraffins (SCCP)

Test Method: With reference to ISO 18219: 2015, analysis was performed by GC-NCI-MS / GC-ECD

Test Item(s)
Alkanes C10-C13, chloro (short-chain chlorinated mg/kg 50 ND paraffins) (SCCPs)

Comment PASS

Notes:

RL (Reporting limit): 50 mg/kg ND = Not Detected(< RL) Requirement: 1500 mg/kg



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overfeaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document not be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date: March 08,2021

Page 20 of 22

Entry 51 of Commission Regulation (EU) 2018/2005 amending Annex XVII Regulation (EC) No 1907/2006 - Phthalates

Test Method: With reference to EN14372: 2004. Analysis was performed by GC-MS.

<u>Test Item(s)</u> Dibutyl Phthalate (DBP)	<u>CAS NO</u> 84-74-2	<u>Unit</u> mg/kg	MDL 30	8+9+10 ND
Benzylbutyl Phthalate (BBP)	85-68-7	mg/kg	30	ND
Bis(2-ethylhexyl) Phthalate (DEHP)	117-81-7	mg/kg	30	ND
Diisobutyl Phthalate (DIBP)	84-69-5	mg/kg	30	ND
Total (DBP + BBP + DEHP+DIBP)	_	mg/kg	30	ND

Comment PASS

Notes:

RL (Reporting limit): 30 mg/kg (each)

ND = Not Detected(< RL)

Requirement: Total (BBP+DBP+DEHP+DIBP) <1000 mg/kg



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document not be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92109241840201TX

Date:March 08,2021

Page 21 of 22



A HIROS Services of Contract S

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification in and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alternation, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention, To check the authoritically of resting /inspection report & certificate, please contact us at telephone (#8675) 8307 4443.

SGS

Test Report

SL92109241840201TX

Date:March 08,2021

Page 22 of 22



The statement of conformity in this test report is only based on measured values by the laboratory and does not take their uncertainties into consideration.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.ferms-e-Documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

of offinition to the control of the



SL92019313799401TX

Date:December 08,2020

Page 1 of 13

HUIZHOU BOWEN MANUFACTURING LIMITED
XINNAN 1ST ROAD, XIANAN VILLAGE, YUANZHOU TOWN, BOLUO COUNTY, HUIZHOU CITY,
GUANGDONG PROVINCE, P.R.CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : COLOR NON-WOVEN FABRIC 16%; MELT BLOWN FABRIC 22%; HOT AIR

COTTON 12%;SKIN FRIENDLY NON-WOVEN FABRIC 10%;EAR THREAD 25%,NOSE CLIP 15% PROTECTIVE RESPIRATOR IN (A)GOLDEN (B)SILVER

Sample Color : (A)GOLDEN; (B)SILVER

(A)COLOR NON-WOVEN FABRIC 16%;MELT BLOWN FABRIC 22%;HOT AIR COTTON 12%;SKIN FRIENDLY NON-WOVEN FABRIC 10%;EAR THREAD

Composition : 25%,NOSE CLIP 15%; (B)COLOR NON-WOVEN FABRIC 16%;MELT BLOWN

FABRIC 22%;HOT AIR COTTON 12%;SKIN FRIENDLY NON-WOVEN FABRIC

10%; EAR THREAD 25%, NOSE CLIP 15%

Style No. : KAZE-01

Manufacturer : HUIZHOU BOWEN MANUFACTURING LIMITED

Country of Destination : United States, EUR

Sample Receiving Date : Dec 02, 2020

Testing Period : Dec 02, 2020 - Dec 08, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Test Performed : Selected test(s) as requested by applicant



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.asp.and, for electronic format documents subject to Terms and Conditions of Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.asp.attention is drawn to the limitation of ilability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction document. This document on the reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Test Report	SL92019313799401TX	Dat	e:December 08,2020	Page 2 of 13
Conclusion	A	В	Remark	

Conclusion	Α	В	
Pentachlorophenol (PCP)	PASS	PASS	
Cadmium (Cd)	PASS	-	
Azo Dyes	PASS	PASS	
Nonylphenol Ethoxylates (NPEOs)	PASS	PASS	
Organotin Compounds	PASS	PASS	
Polycyclic Aromatic Hydrocarbons (PAHs)	PASS	<i>(, -</i>	
Short Chain Chlorinated Paraffins (SCCP)	PASS	—	
Phthalates	PASS	-	

Remark(s): PASS=Meet Client's/General Requirement

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Lily Wang (Account Manager)

Inspection & Testing Services

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits or Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document on the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

198 Kezhu Rozd, Scientech Park Guangthou Economic&Technology Development District, Guangthou, China 510663 (86–20) 82155555 (86–20) 82075169 www.sgsgroup.com.cn 中国 · 广州 · 经济技术开发区科学城科珠路198号 邮编: 510663 (86–20) 82155555 (86–20) 82075169 e sgs.china@sgs.com



SL92019313799401TX

Date:December 08,2020

Page 3 of 13

COMPONENT LIST / List of Materials

Sample No.	Component No.	Description	Material	Color	Remark
Α	1	Outer non woven fabric	Synthetic Fibers	Golden	
Α	3	Hot air cotton fabric	Blended Fibers	White	B material type same as A
Α	4	Melt-blown non woven fabric	Synthetic Fibers	White	B material type
	т	Wick blown non weven labile	Cyritiicac i ibcio	VVIIIC	same as A
A	5	Lining non woven fabric	Synthetic Fibers	White	B material type
	3	Lifting flort wover rabite	Syrillietic i ibers	VVIIILE	same as A
Α	6	Round band	Synthetic Fibers	Natural	
Α	8	Foam with white layer backing	Foam	Black	B material type same as A
Α	9	Adjustable clip	Plastics	White	B material type
А	9	Aujustable clip	riasiics	vviiite	same as A
A	10	Nose clip	Plastics	White	B material type
A	10	Nose clip	riasiics	vviile	same as A
В	2	Outer non woven fabric	Synthetic Fibers	Silvery	
В	7	Round band	Synthetic Fibers	Grey	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's Sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized attention, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law, unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) t



SL92019313799401TX

Date:December 08,2020

Page 4 of 13

Test Result

European Regulation POPs (EU) 2019/1021 - Pentachlorophenol (PCP

Test Method: Modified §64 LFGB, BVL, B 82.02.8-2001 Alkaline (KOH) digestion, analysis was performed

by GC-ECD or GC-MS.

Test Item(s) Pentachlorophenol (PCP) CAS NO

<u>Unit</u>

MDL <u>1+2</u>

<u>6+7</u>

3+4+5 ND

Comment

87-86-5

mg/kg

0.15 ND **PASS**

ND **PASS**

PASS

Notes:

RL (Reporting limit): 0.15 mg/kg

ND = Not Detected(< RL)

Requirement: Banned(< 0.5 mg/kg)

Entry 23 of Commission Regulation (EU) No 835/2012, (EU) No 494/2011 and (EU) 2016/217 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Cadmium(Cd)

Test Method: With reference to EN 1122: 2001, Method B, analysis was performed by AAS.

Test Item(s) Cadmium (Cd) Comment

MDL 8+9+10 ND

mg/kg

PASS

Notes:

RL (Reporting limit): 5 mg/kg ND = Not Detected(< RL) Requirement: 100 mg/kg





SL92019313799401TX

Date:December 08,2020

Page 5 of 13

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Direct reduction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

Test Item(s)	CAS_NO	<u>Unit</u>	MDL	<u>1+2</u>	<u>6+7</u>
4-Aminobiphenyl	92-67-1	mg/kg	5	ND	ND
Benzidine	92-87-5	mg/kg	5	ND	ND ¹
4-chloro-o-toluidine	95-69-2	mg/kg	5	ND	ND
2-naphthylamine	91-59-8	mg/kg	5	ND	ND
o-aminoazotoluene	97-56-3	mg/kg	5	ND	ND
5-nitro-o-toluidine / 2-Amino-4-nitrotolu	uene 99-55-8	mg/kg	5	ND	ND
4-chloroaniline	106-47-8	mg/kg	5	ND	ND
4-methoxy-m-phenylenediamine /	615-05-4	mg/kg	5	ND	ND
2,4-Diaminoanisole					
4,4'-diaminodiphenylmethane, MDA	101-77-9	mg/kg	5	ND	ND
3,3'-dichlorobenzidine	91-94-1	mg/kg	5	ND	ND
3,3'-dimethoxybenzidine	119-90-4	mg/kg	5	ND	ND
3,3'-dimethylbenzidine	119-93-7	mg/kg	5	ND	ND
4,4'-methylenedi-o-toluidine/3,3'-Dime	thyl-4,4' 838-88-0	mg/kg	5	ND	ND
-diaminodiphenylmethane					
p-cresidine	120-71-8	mg/kg	5	ND	ND
4,4'-methylene-bis-(2-chloroaniline)	101-14-4	mg/kg	5	ND	ND
4,4'-oxydianiline	101-80-4	mg/kg	5	ND	ND
4,4'-thiodianiline	139-65-1	mg/kg	5	ND	ND
o-toluidine	95-53-4	mg/kg	5	ND	ND
4-methyl-m-phenylenediamine /	95-80-7	mg/kg	5	ND	ND
2,4-Toluylendiamine, TDA					
2,4,5-trimethylaniline	137-17-7	mg/kg	5	ND	ND
4-aminoazobenzene	60-09-3	mg/kg	5	ND	ND
O-Anisidine	90-04-0	mg/kg	5	ND	ND
Comment		V		PASS	PASS



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and colligations under the transaction documents. This document on the reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92019313799401TX

Date:December 08,2020

Page 6 of 13

Notes:

RL (Reporting limit): 5 mg/kg (for individual compound)
ND = Not Detected(< RL)

Requirement: 30 mg/kg (for individual compound)

(1)Method A is direct reduction, direct reduction refers to the extraction and reduction according to ISO 14362-1:2017 clause 10.2 and relevant clauses. Method B is colorant extraction, colorant extraction refers to the colourant extraction and subsequent reduction according to ISO 14362-1:2017 clause 10.1 and relevant clauses.

(2)The ISO 14362-1:2017 methods will enable further cleavage of 4 aminoazobenzene to non forbidden amines: aniline and 1,4 phenylenediamine, therefore, the test method of ISO 14362-3:2017 was employed to verify the presence of 4 aminoazobenzene.

(3) Max. limit specified by entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 (previously restricted under Directive 2002/61/EC).

(4)Whenever 4-aminodiphenyl (CAS number 92-67-1), 2-naphylamine (CAS number 91-59-8) and 4-methoxy-m-phenylene-diamine (CAS number 615-05-4) is found, the use of banned azo colorants cannot be reliably ascertained without additional information, e.g. the chemical structure of the colorants used. In case polyurethane materials are used, e.g. PU foams and coatings and in prints, it cannot be ruled out that certain amines, e.g. 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) and 2,4-toluylen-diamine (TDA, CAS number 95-80-7) are released from the PU component and not from a banned azo colorant. In case of pigment prints care has to be taken that 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) is not released from a source of banned azo colorants but from e.g. a chemical fixing agent.



Unless otherwise agreed in wrung, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on requiest or accessible at http://www.sgs.com/en/Tems-and-Conditions/Tems-e-Document.asp xubject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Tems-and-Conditions/Terms-e-Document.asp xtlention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any, The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authoriticity of resting fullspection report & certificate, presonation as a legion of the content of the surface of the surface



SL92019313799401TX

Date:December 08,2020

Page 7 of 13

Entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Azo Dyes(Colorant extraction approach)

Test Method: According to EN ISO 14362-1:2017, analysis was performed by GC-MS/ HPLC-DAD.

Determination of 4-aminoazobenzene (CAS No.:60-09-3) - EN ISO 14362-3:2017, analysis was

performed by GC-MS/ HPLC-DAD.

CAS_NO	<u>Unit</u>	<u>MDL</u>	<u>1+2</u>	<u>6+7</u>
92-67-1	mg/kg	5	ND	ND .
92-87-5	mg/kg	5	ND	ND
95-69-2	mg/kg	5	ND	ND
91-59-8	mg/kg	5	ND	ND-
97-56-3	mg/kg	5	ND	ND
iene 99-55-8	mg/kg	5	ND	ND
106-47-8	mg/kg	5	ND	ND
615-05-4	mg/kg	5	ND	ND
101-77-9	mg/kg	5	ND	ND
91-94-1	mg/kg	5	ND	ND
119-90-4	mg/kg	5	ND	ND
119-93-7	mg/kg	5	ND	ND
thyl-4,4' 838-88-0	mg/kg	5	ND	ND
				(-)
120-71-8	mg/kg	5	ND	ND
101-14-4	mg/kg	5	ND	ND
101-80-4	mg/kg	5	ND	ND
139-65-1	mg/kg	5	ND	ND
95-53-4	mg/kg	5	ND	ND
95-80-7	mg/kg	5	ND	ND
137-17-7	mg/kg	5	ND	ND
60-09-3	mg/kg	5	ND	ND
90-04-0	mg/kg	5	ND	ND
			PASS	PASS
	92-67-1 92-87-5 95-69-2 91-59-8 97-56-3 99-55-8 106-47-8 615-05-4 101-77-9 91-94-1 119-90-4 119-93-7 thyl-4,4' 838-88-0 120-71-8 101-14-4 101-80-4 139-65-1 95-53-4 95-80-7 137-17-7 60-09-3	92-67-1 mg/kg 92-87-5 mg/kg 95-69-2 mg/kg 97-56-3 mg/kg 97-56-3 mg/kg 106-47-8 mg/kg 615-05-4 mg/kg 119-90-4 mg/kg 119-93-7 mg/kg 119-93-7 mg/kg 101-14-4 mg/kg 101-80-4 mg/kg 139-65-1 mg/kg 95-80-7 mg/kg 137-17-7 mg/kg	92-67-1 mg/kg 5 92-87-5 mg/kg 5 95-69-2 mg/kg 5 91-59-8 mg/kg 5 97-56-3 mg/kg 5 106-47-8 mg/kg 5 615-05-4 mg/kg 5 119-90-4 mg/kg 5 119-93-7 mg/kg 5 120-71-8 mg/kg 5 101-14-4 mg/kg 5 101-80-4 mg/kg 5 139-65-1 mg/kg 5 95-53-4 mg/kg 5 137-17-7 mg/kg 5	92-67-1 mg/kg 5 ND 92-87-5 mg/kg 5 ND 95-69-2 mg/kg 5 ND 91-59-8 mg/kg 5 ND 97-56-3 mg/kg 5 ND 106-47-8 mg/kg 5 ND 615-05-4 mg/kg 5 ND 119-90-4 mg/kg 5 ND 119-93-7 mg/kg 5 ND 120-71-8 mg/kg 5 ND 120-71-8 mg/kg 5 ND 120-71-8 mg/kg 5 ND 133-65-1 mg/kg 5 ND 137-17-7 mg/kg 5 ND



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.asp.and, for electronic format documents subject to Terms and Conditions of Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.asp.attention is drawn to the limitation of ilability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction document. This document on the reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92019313799401TX

Date:December 08,2020

Page 8 of 13

Notes:

RL (Reporting limit): 5 mg/kg (for individual compound)
ND = Not Detected(< RL)

Requirement: 30 mg/kg (for individual compound)

(1)Method A is direct reduction, direct reduction refers to the extraction and reduction according to ISO 14362-1:2017 clause 10.2 and relevant clauses. Method B is colorant extraction, colorant extraction refers to the colourant extraction and subsequent reduction according to ISO 14362-1:2017 clause 10.1 and relevant clauses.

(2)The ISO 14362-1:2017 methods will enable further cleavage of 4 aminoazobenzene to non forbidden amines: aniline and 1,4 phenylenediamine, therefore, the test method of ISO 14362-3:2017 was employed to verify the presence of 4 aminoazobenzene.

(3) Max. limit specified by entry 43 of Regulation (EC) No 552/2009 amending Annex XVII of REACH Regulation (EC) No 1907/2006 (previously restricted under Directive 2002/61/EC).

(4)Whenever 4-aminodiphenyl (CAS number 92-67-1), 2-naphylamine (CAS number 91-59-8) and 4-methoxy-m-phenylene-diamine (CAS number 615-05-4) is found, the use of banned azo colorants cannot be reliably ascertained without additional information, e.g. the chemical structure of the colorants used. In case polyurethane materials are used, e.g. PU foams and coatings and in prints, it cannot be ruled out that certain amines, e.g. 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) and 2,4-toluylen-diamine (TDA, CAS number 95-80-7) are released from the PU component and not from a banned azo colorant. In case of pigment prints care has to be taken that 4,4'-methylene-dianiline (MDA, CAS number 101-77-9) is not released from a source of banned azo colorants but from e.g. a chemical fixing agent.



Unless otherwise agreed in wrung, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on requiest or accessible at http://www.sgs.com/en/Tems-and-Conditions/Tems-e-Document.asp xubject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Tems-and-Conditions/Terms-e-Document.asp xtlention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions. If any, The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authoriticity of resting fullspection report & certificate, presonation as a legion of the content of the surface of the surface



SL92019313799401TX

Date:December 08,2020

Page 9 of 13

Entry 46a of Commission Regulation (EU) 2016/26 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Nonylphenol Ethoxylates(NPEOs)

Test Method: With reference to ISO 18254-1:2016, analysis was performed by LC-MS

Test Item(s)	<u>Unit</u>	<u>MDL</u>	<u>1+2</u>	<u>6+7</u>	<u>3+4+5</u>
Nonylphenol Ethoxylate (NPEO)	mg/kg	30	ND	ND	ND
Comment			PASS	PASS	PASS

Notes:

RL (Reporting limit) :30 mg/kg ND = Not Detected(< RL) Requirement: 100 mg/kg



Omess driefwise agreed in wrung, this sought of the Company suggest to its sceneral Conditions of Service prime subject to Text sale and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Document aspx. Attention is drawn to the limitation of liability, indemnification and pursification issues defined therein. Any holder of this document advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits collected that the company of the company of the company and the contained appearance of the company and the contained appearance of the company and the contained appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



\$L92019313799401TX

Date:December 08,2020

Page 10 of 13

Entry 20 of Regulation (EC) No 276/2010 amending Annex XVII of REACH Regulation (EC) No 1907/2006 - Organotin Compounds

Test Method: SGS In-house method (GZTC CHEM-TOP-031, with reference to ISO 17353:2004), analysis was performed by GC-MS.

Test Item(s)	<u>Unit</u>	<u>MDL</u>	<u>1+2</u>	<u>6+7</u>	<u>3+4+5</u>
Dibutyl tin (DBT) by weight of Tin	mg/kg	100	ND	ND	ND
Dioctyl tin (DOT) by weight of Tin	mg/kg	100	ND	ND	ND
Tributyl tin (TBT) by weight of Tin	mg/kg	100.00	ND	ND	ND
Triphenyl tin (TPhT) by weight of Tin	mg/kg	100.00	ND	ND	ND
Tricyclohexyltin (TCyT) by weight of Tin	mg/kg	100.00	ND	ND	ND
Trioctyltin (TOT) by weight of Tin	mg/kg	100.00	ND	ND	ND
Tripropyltin (TPT) by weight of Tin	mg/kg	100	ND	ND	ND
Trimethyltin(TMT) by weight of Tin	mg/kg	100.00	ND	ND	ND
Σ of Tri substituted organotin compounds calculated	mg/kg	100	ND	ND	ND
Comment					
as tin			PASS	PASS	PASS

Test Item(s)	<u>Unit</u>	MDL	<u>8+9+10</u>
Dibutyl tin (DBT) by weight of Tin	mg/kg	100	ND
Dioctyl tin (DOT) by weight of Tin	mg/kg	100	ND
Tributyl tin (TBT) by weight of Tin	mg/kg	100.00	ND
Triphenyl tin (TPhT) by weight of Tin	mg/kg	100.00	ND
Tricyclohexyltin (TCyT) by weight of Tin	mg/kg	100.00	ND
Trioctyltin (TOT) by weight of Tin	mg/kg	100.00	ND
Tripropyltin (TPT) by weight of Tin	mg/kg	100	ND
Trimethyltin(TMT) by weight of Tin	mg/kg	100.00	ND
Σ of Tri substituted organotin compounds calculated	mg/kg	100	ND
Comment			
as tin			PASS

Notes:

RL (Reporting limit): 100 mg/kg (for individual compound)

ND = Not Detected (< RL)

Requirement:

Tri substituted Organotin compound (TBT,TPhT,TCyT,TPT,TOT,TMT): 1000 mg/kg by weight of

tin (sum)

DBT: 1000 mg/kg by weight of tin DOT: 1000 mg/kg by weight of tin



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed versilead, available on request or accessible at http://www.sas.com/en/Terms-and-Conditions.aspx, and, for electronic format documents, this this ways, com/en/Terms-and-Conditions for Electronic Documents at http://www.sas.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a rensaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the eaults shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92019313799401TX

Date:December 08,2020

Page 11 of 13

Entry 50 of Commission Regulation (EU) No 1272/2013 amending Annex XVII of REACH Regulation (EC)

1907/2006 - Polycyclic Aromatic Hydrocarbons(PAHs)

Test Method: With reference to AfPS GS 2019:01 PAK, analysis was performed by GC-MS.

Test Item(s)	CAS_NO	<u>Unit</u>	<u>MDL</u>	<u>8+9</u>
Benzo(a)anthracene(BaA)	56-55-3	mg/kg	0.1	ND
Chrysene(CHR)	218-01-9	mg/kg	0.1	ND
Benzo(b)fluoranthene(BbF)	205-99-2	mg/kg	0.1	ND
Benzo(j)fluoranthene(BjF)	205-82-3	mg/kg	0.1	ND
Benzo(k)fluoranthene(BkF)	207-08-9	mg/kg	0.1	ND
Benzo(a)pyrene(BaP)	50-32-8	mg/kg	0.1	ND
Benzo(e)pyrene(BeP)	192-97-2	mg/kg	0.1	ND
Dibenzo(a,h)anthracene(DBA)	53-70-3	mg/kg	0.1	ND
Comment				PASS

Notes:

RL (Reporting limit): 0.1 mg/kg (each)

ND = Not Detected(< RL)
Requirement: 1 mg/kg (each)

European Regulation POPs (EU) 2019/1021 - Short Chain Chlorinated Paraffins (SCCP)

Test Method: With reference to ISO 18219: 2015, analysis was performed by GC-NCI-MS / GC-ECD.

Test Item(s)	<u>Unit</u>	MDL <u>8+9+10</u>
Alkanes C10-C13, chloro (short-chain chlorinated	mg/kg	50 ND
Comment		
paraffins) (SCCPs)		PASS

Notes:

RL (Reporting limit): 50 mg/kg ND = Not Detected(< RL) Requirement: 1500 mg/kg



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for the Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.attention is drawn to the limitation of ilability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information only and within the limits (Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content of appearance of this document is unawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SL92019313799401TX

Date:December 08,2020

Page 12 of 13

Entry 51 of Commission Regulation (EU) 2018/2005 amending Annex XVII Regulation (EC) No 1907/2006 - Phthalates

Test Method: With reference to EN14372: 2004. Analysis was performed by GC-MS.

Test Item(s)	CAS_NO	<u>Unit</u>	<u>MDL</u>	<u>8+9+10</u>
Dibutyl Phthalate (DBP)	84-74-2	mg/kg	30.000	ND
Benzylbutyl Phthalate (BBP)	85-68-7	mg/kg	30.000	ND
Bis(2-ethylhexyl) Phthalate (DEHP)	117-81-7	mg/kg	30.000	ND
Diisobutyl Phthalate (DIBP)	84-69-5	mg/kg	30.000	ND
Total (DBP + BBP + DEHP+DIBP)	-	mg/kg	30	ND
Comment				PASS

Notes:

RL (Reporting limit): 30 mg/kg (each)

ND = Not Detected(< RL)

Requirement: Total (BBP+DBP+DEHP+DIBP) <1000 mg/kg

Remarks:

(1) 1 mg/kg = 0.0001%

(2) MDL = Method Detection Limit

(3) ND = Not Detected (< MDL)

Inspection & Testing Services


Oness otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format document subject to Terms and Conditions of Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditio



SL92019313799401TX

Date:December 08,2020

Page 13 of 13



The statement of conformity in this test report is only based on measured values by the laboratory and does not take their uncertainties into consideration.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.
Attention is drawn to the limitation of ilability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exported to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are relaimed for 30 days only.

or email: CN.Deccheck@uss.com 198 Rezhu Roud, Scentach Park (sandphue Epozonice Rechalogy Development Dishict, Giangrahou, China 510663 t (86–20), 82155555 f (86–20), 82075169 www.sgsgroup.com.cn 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86–20), 82155555 f (86–20), 82075169 e sgs.china@sgs.com



SL52105232489101TX



Date:March 03,2021



国际互认 检测 TESTING CNAS L0599

Page 1 of 2

HUIZHOU BOWEN MANUFACTURING LIMITED

XINNAN 1ST ROAD, XIANAN VILLAGE, YUANZHOU TOWN, BOLUO COUNTY, HUIZHOU CITY GUANGDONG PROVINCE, P.R.CHINA

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description (A)Kaze Face Mask (Claimed Type II)

Sample Color (A)Citrus Orange

(A)25%ear thread, 22%melt blown fabric; 16%Color non-woven fabric; 15%nose Composition

clip; 12%hot air cotton; 10%skin friendly non-woven fabric

Style No. KAZE-01 2020.12 Lot No.

Manufacturer Huizhou Bowen Manufacturing Limited

Country of Destination Europe, USA

Sample Receiving Date Feb 07, 2021

Testing Period Feb 08, 2021 - Mar 03, 2021

Test Result(s) Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Test Performed Selected test(s) as requested by applicant

Comment:

EN 14683:2019+AC:2019 Medical Face Masks-Requirements and Test	(A)
<u>Methods</u>	
Clause 5.2 Performance Requirement	
Clause 5.2.2 Bacterial filtration efficiency (BFE)	EXCLUDED
Clause 5.2.3 Breathability	EXCLUDED
Clause 5.2.4 Splash Resistance	EXCLUDED
Clause 5.2.5 Microbial Cleanliness	M
Clause 5.2.6 Biocompatibility	EXCLUDED

Remark: M=Meet EN 14683:2019+AC:2019 Performance Requirement (Type II) F=Below EN 14683:2019+AC:2019 Performance Requirement (Type II)

Signed for and on behalf of

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center

Sara Guo (Account Executive)

Dongjing Liu (Authorized Signatory)

SGS does not verify authenticity of any Brand/Trademark of products. Buyers must check if the product is genuine with the Brand/Trademark owner directly.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

3rdBuilding,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666

f (86-21) 64958763 f (86-21) 64958763 www.sgsgroup.com.cn e sgs.china@sgs.com



SL52105232489101TX

Date:March 03,2021

Page 2 of 2

Test Result

EN 14683:2019+AC:2019 Medical Face Masks-Requirements and Test Methods

Clause 5.2 Performance Requirement

Clause 5.2.5 Microbial Cleanliness

(EN 14683:2019+AC:2019 Annex D and EN ISO 11737-1:2018)

Sample: A

Test Specimen#	Mask Weight(g)	Total Bioburden, (CFU/mask)	Total Bioburden, (CFU/g)
1#	6.77	33	4.87
2#	7.01	27	3.85
3#	6.67	27	4.05
4#	7.05	36	5.11
5#	6.76	27	3.99

Remark: Performance Requirement: Type I≤30 CFU/g, Type II≤30 CFU/g, Type IIR≤30 CFU/g



Product information is provided by applicant without verification of authentication of the brand.

The statement of conformity in this test report is only based on measured values by the laboratory and does not take their uncertainties into consideration.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

3[™]Building,No.889,Yishan Road,Xuhui District Shanghai,China 200233 中国・上海・徐汇区宜山路889号3号楼 邮编: 200233 t (86-21) 61402666 t (86-21) 61402666 f (86-21) 64958763 f (86-21) 64958763 www.sgsgroup.com.cn e sgs.china@sgs.com







This is to certify that: Huizhou Bowen Manufacturing Ltd

Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County

Huizhou City Guangdong 516123 China

Holds Certificate Number: CE 729875

In respect of:

Model: Kaze-05 Face mask To technical specification Annex II (EHSR) of the PPE Regulation (EU) 2016/425 PPE for use by healthcare professionals as per Commission recommendation 2020/403

on the basis that BSI carried out the relevant Type Examination procedures under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex V (Module B) and meets the relevant health and safety requirements specified in Annex II

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Drs. Dave Hagenaars, Managing Director

First Issued: 2021-01-25 Latest Issue: 2021-01-25

Effective Date: 2021-01-25 Expiry Date: 2022-01-25

Page: 1 of 3

...making excellence a habit."



No. CE 729875

Product Specification

Product Name: Kaze Protective Respirator.

Product Type: Particulate filtering half masks for use by Healthcare professionals.

Model: Kaze-05

Colour Variants: 18 Colour Variants - White, Dove Grey, Forest Pine, Sweet Pea, Powder Blue, Royal

Blue, Racing Red, Fuchsia, Maroon, Ultraviolet, Rose Quartz, Sandy Beige, Citrus

Orange, Champagne, Natural Sand, Light Blush, Espresso and Silver Grey

Classification: FFP2 NR

Technical Specification: Technical specification to satisfy Annex II of the PPE Regulation (EU) 2016/425.

Product Description: The respirator is non-reusable, secured to the face of the user by a pair of

> elasticated ear straps, and has no exhalation valve. The respirator is FFP2 NR class, vertical fold flat type. The Respirator has 18 Colour Variants; White, Dove Grey, Forest Pine, Sweet Pea, Powder Blue, Royal Blue, Racing Red, Fuchsia, Maroon, Ultraviolet, Rose Quartz, Sandy Beige, Citrus Orange,

Champagne, Natural Sand, Light Blush, Espresso and Silver Grey.

The respirator listed on this certificate is for use by healthcare workers, first responders and other personnel involved in the efforts to contain the COVID-19

virus and avoid its further spread.

The product covered by this certificate is not approved for industrial applications and

the certificate is only valid as long as EU Commission recommendation sheet

2020/403 remains applicable.

Product Assessments: BSI's PPE for Healthcare Professionals 2020/403 – RPE Technical Specification.

First Issued: 2021-01-25 Effective Date: 2021-01-25 Latest Issue: 2021-01-25 Expiry Date: 2022-01-25

Page: 2 of 3



No. CE 729875

Certificate Administration Details

Technical File Reference: Huizhou Bowen Manufacturing Ltd, Kaze-05

Certificate Amendment Record:

Issue date	Comments		BSI Review No.
January 2021	First issue.		2797:20:3218633

Certificate validity

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspect of the overall process utilised in the manufacture of the product, failure to do so could invalidate the Certificate in respect of product manufactured following the introduction of such changes.

The validity of the Certificate for the products is also dependent on the maintenance of the EU Conformity to Type based on Internal Production Control plus supervised product checks at random intervals, Annex VII (Module C2) as referenced on BSI issued Certificate CE 729876.

First Issued: 2021-01-25 Effective Date: 2021-01-25 Latest Issue: 2021-01-25 Expiry Date: 2022-01-25

Page: 3 of 3







Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

This is to certify that: Huizhou Bowen Manufacturing Ltd

Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County

Huizhou City Guangdong 516123 China

Holds Certificate Number: CE 729876

In respect of:

For the manufacture of particulate respirators to technical specification to satisfy Annex II of the PPE Regulation (EU) 2016/425.

on the basis that BSI carried out the supervised production checks at random intervals under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex VII (Module C2)

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Drs. Dave Hagenaars, Managing Director

First Issued: 2021-01-25 Latest Issue: 2021-01-25

Effective Date: 2021-01-25 Expiry Date: 2022-01-25

Page: 1 of 3

...making excellence a habit."



Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

No. CE 729876

Product manufactured by:

Huizhou Bowen Manufacturing Ltd. Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County Huizhou City Guangdong 516123 China

Product details

The respiratory protective device covered by the scope of this Module C2 Certificate and the Technical Specification to which the product is manufactured are as follows:

Product type: Particulate filtering half masks for use by Healthcare professionals.

Model and classifications: Kaze-05 FFP2 NR

Colour Variants: 18 Colour Variants - White, Dove Grey, Forest Pine, Sweet Pea, Powder Blue,

Royal Blue, Racing Red, Fuchsia, Maroon, Ultraviolet, Rose Quartz, Sandy Beige, Citrus Orange, Champagne, Natural Sand, Light Blush, Espresso and Silver Grey.

Technical Specification: Technical specification to satisfy Annex II of the PPE Regulation (EU) 2016/425.

BSI's PPE for Healthcare Professionals 2020/403 - RPE Technical Specification.

First Issued: 2021-01-25 Effective Date: 2021-01-25 Latest Issue: 2021-01-25 Expiry Date: 2022-01-25

Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

No. CE 729876

Certificate Administration Details:

Certificate Amendment Record and BSI internal Review relating to this Certificate

Issue date	Comments		BSI Review No.
January 2021	First issue.		2797:20:3218634

Certificate validity

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspects of the overall quality system utilized in the manufacture of the products, failure to do so could invalidate the Certificate in respect of product manufactured after the introduction of such changes.

Effective Date: 2021-01-25 First Issued: 2021-01-25 Latest Issue: 2021-01-25 Expiry Date: 2022-01-25

Page: 3 of 3

EU DECLARATION OF CONFORMITY

This declaration of conformity is issued under the sole responsibility of the manufacturer:

Manufacturer and address	Huizhou Bowen Manufacturing Limited
	Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo
	County, Huizhou City, Guangdong Province, P.R.China
Product name	Kaze Protective Respirator
Model/ Serial No.	KAZE-05
Technical Reference:	EN 149:2001+A1:2009
Applicable Regulation:	PPE Regulation 2016/425
Notified body for EU type-	BSI Group - NB 2797
examination (Module B)	The Netherlands BV, Say Building, John M Keynesplein 9,
.6,	1066 EP, Amsterdam, Netherlands
Notified body for EU type-	BSI Group - NB 2797
examination (Module C2)	The Netherlands BV, Say Building, John M Keynesplein 9,
	1066 EP, Amsterdam, Netherlands
Certificate number	CE 729875 & CE 729876

We declared that given information on the above statement and attached documents/records are true and correct to the best of our knowledge.

Signed for and on behalf of: Huizhou Bowen Manufacturing Limited

29th April, 2021

Mr. Tse Ka Fai

造有限 Director of Sales Operation







This is to certify that: Huizhou Bowen Manufacturing Ltd

> Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County

Huizhou City Guangdong 516123 China

Holds Certificate Number: CE 749147

In respect of:

Respiratory protective devices - Filtering half masks to protect against particles To EN 149:2001+A1:2009

Model: Kaze-05.

on the basis that BSI carried out the relevant Type Examination procedures under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex V (Module B) and meets the relevant health and safety requirements specified in Annex II

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Drs. Dave Hagenaars, Managing Director

First Issued: 2021-08-10 Latest Issue: 2021-08-10

Effective Date: 2021-08-10 Expiry Date: 2026-08-10

Page: 1 of 3

...making excellence a habit.™



No. CE 749147

Product Specification

Product Type: Filtering half masks to protect against particles.

Model: Kaze-05

Product description: The mask is designed to protect against solid and non-volatile liquid particles.

The model is a non-valved, non-sterile device for single shift use (denoted by the classification symbol NR). The retention system consists of 2 ear bands that

incorporate length adjusters.

The model is available in the following colours:

White Forest Pine Sweet Pea Dove Grey Powder Blue Royal Blue Racing Red **Fuchsia** Maroon Ultraviolet Rose Quartz Sandy Beige Citrus Orange Champagne Natural Sand Light Blush Cobalt Blue Espresso Silver Grey Purple Berry

Spearmint Key Lime Bubblegum **Ivory**

Onxy

Technical specifications: EN 149:2001+A1:2009 -

Respiratory protective devices – Filtering half masks to protect against particles.

EN 149 Classification: FFP2 NR

First Issued: 2021-08-10 Effective Date: 2021-08-10 Latest Issue: 2021-08-10 Expiry Date: 2026-08-10

Page: 2 of 3

No. CE 749147

Certificate Administration Details

Technical File Reference: Kaze-05.

Certificate Amendment Record:

Issue date Comments **BSI Review Number**

August 2021

First issue under PPE Regulation (EU) 2016/425. The product was initially Certified by BSI as a mask for protection against Covid-19, Certificate CE 729875 refers.

2797:21:3384908

Certificate validity

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspect of the overall processes utilised in the manufacture of the product, failure to do so could invalidate the Certificate in respect of product manufactured following the introduction of such changes.

The validity of the Certificate for the products is also dependent on the maintenance of the EU Conformity to Type based on Internal Production Control plus supervised product checks at random intervals, Annex VII (Module C2) as referenced on BSI issued Certificate CE 749149.

First Issued: 2021-08-10 Effective Date: 2021-08-10 Latest Issue: 2021-08-10 Expiry Date: 2026-08-10

Page: 3 of 3







Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

This is to certify that: Huizhou Bowen Manufacturing Ltd

> Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County

Huizhou City Guangdong 516123 China

Holds Certificate Number: CE 749149

In respect of:

Respiratory protective devices to EN 149:2001+A1:2009 -Filtering half masks to protect against particles.

on the basis that BSI carried out the supervised production checks at random intervals under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex VII (Module C2)

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Drs. Dave Hagenaars, Managing Director

First Issued: 2021-08-10 Latest Issue: 2021-08-10

Effective Date: 2021-08-10 Expiry Date: 2026-08-10

Page: 1 of 3

...making excellence a habit.™



Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

No. CE 749149

Design and Production Location:

Huizhou Bowen Manufacturing Ltd Xinnan 1st Road, Xianan Village Yuanzhou Town, Boluo County **Huizhou City** Guangdong 516123 China

Scope of Certificate

The respiratory protective device covered by the scope of this Module C2 Certificate and the Technical Specification to which the product is manufactured are as follows:

Filtering half mask to protect against particles. **Product Type:**

Technical specification: EN 149:2001+A1:2009 -

Respiratory protective devices – Filtering half masks to protect against particles.

Model: Kaze-05

The model is available in the following colours:

White **Dove Grey** Forest Pine Sweet Pea Racing Red Powder Blue Royal Blue **Fuchsia** Rose Quartz Maroon Ultraviolet Sandy Beige Light Blush Citrus Orange Champagne Natural Sand Espresso Silver Grey Cobalt Blue **Purple Berry**

Spearmint Bubblegum Key Lime **Ivory**

Onxy

EN 149 classifications: FFP2 NR.

First Issued: 2021-08-10 Effective Date: 2021-08-10 Latest Issue: 2021-08-10 Expiry Date: 2026-08-10

Conformity to Type based on Internal Production Control plus supervised product checks at random intervals

No. CE 749149

Certificate Administration Details

Certificate Administration Record:

BSI Project Ref. Issue date **Comments** 2797:21:3384910 August 2021 First Issue.

Certificate validity

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspect of the overall process utilised in the manufacture of the products, failure to do so could invalidate the Certificate in respect of product manufactured following the introduction of such changes.

The validity of the Certificate is also dependent on the maintenance of a documented quality system.

First Issued: 2021-08-10 Effective Date: 2021-08-10 Latest Issue: 2021-08-10 Expiry Date: 2026-08-10

Page: 3 of 3

EU DECLARATION OF CONFORMITY

This declaration of conformity is issued under the sole responsibility of the manufacturer:

Manufacturer and address	Huizhou Bowen Manufacturing Limited
	Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo
	County, Huizhou City, Guangdong Province, P.R.China
Product name	Kaze Protective Respirator
Model/ Serial No.	KAZE-05
Technical Reference:	EN 149:2001+A1:2009
Applicable Regulation:	PPE Regulation 2016/425
Notified body for EU type-	BSI Group - NB 2797
examination (Module B)	The Netherlands BV, Say Building, John M Keynesplein 9,
.6,	1066 EP, Amsterdam, Netherlands
Notified body for EU ongoing	BSI Group - NB 2797
production surveillance	The Netherlands BV, Say Building, John M Keynesplein 9,
(Module C2)	1066 EP, Amsterdam, Netherlands
Certificate number	CE 749147 & CE 749149

We declared that given information on the above statement and attached documents/records are true and correct to the best of our knowledge.

Signed for and on behalf of: Huizhou Bowen Manufacturing Limited

29th April, 2021

Director of

Mr. Tse Ka Fai

Sales Operation





Introduction

This report has been prepared by Paul Waller and relates to the activity detailed below:

Job/Registration	n Details	Client Details	
Job number: Job type: Start Date: Test type: Sample ID: Registration: Scheme: Protocol: Scheme Manager:	3218630-R2 Testing Samples Submitted 07/09/2020 Type Retest 10190086, 10192109 and 10193209 CE 729875 Positive pressure RPE PP123 Nathan Shipley	Huizhou Bowen Manufacturing Ltd Xinnan 1st Road Xianan Village Yuanzhou Town Boluo County Huizhou City Guangdong 516123 China	

The report has been approved for issue by T Wicksey - Senior Test Engineer

Approved For Issue			
2064	10	Issue Date: 20 October 2020	16

Objectives.

This is an independent retest evaluation to only certain clauses or sub-clauses of the agreed specification in accordance with the following test programme:

BSI COVID-19 filtering face piece technical specification, for COVID-19 masks for use by healthcare workers Retest due to failures under BSI job numbers 3218630 and 3218630-R1.


Product Scope.

COVID-19 masks for use by healthcare workers

Report Summary.

The samples were received on 3 September 2020 and the testing was started on 7 September 2020.

The samples submitted complied with the requirements of the test work conducted.





Test Samples.

Sample ID	ER Number	Description	
1 to 19	10190086, 10192109 and 10193209	Model: Kaze	

Description of Test Samples.

Sample Description	4/	4/	
COVID-19 masks for use by healthcare v	vorkers:		
Model: Kaze			

HATE HATE HATE HATE

HATE HATE HATE

HATE HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

HATE

age 3 of 10 ...making excellence a habit.



Test Requirements.

Testing in accordance with BSI COVID-19 filtering face piece technical specification Technical testing specification for COVID-19 masks for use by healthcare workers

Technical testing specification for COVID		e workers				
EN 149:2001 + A1:2009	EN 149:2001 + A1:2009	Requirement	Assessment			
Performance requirement 7.7 Practical performance The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard. Where practical performance tests show the apparatus has imperfections related to wearer's acceptance, the test house shall provide full details of those parts of the practical performance tests which revealed these imperfections.	Test method clause Testing shall be done in accordance with 8.4.	During the tests the particle filtering half mask shall be subjectively assessed by the wearer and after the test, comments on the following shall be recorded: a) head harness comfort; b) security of fastenings; c) field of vision; d) any other comments reported by the wearer on request.	Pass			
2 test subjects, masks tested 'As received'	161	16	4			
7.9 Leakage 7.9.1 Total inward leakage 3 or 5 subjects with samples AR (see criteria)	Testing shall be done in accordance with 8.5.	Test 3 subjects - If the 3 tests produce results between 6% and 8% mean or individual results over 11%, test 5 subjects If 5 tests undertaken;	The			
	16	23 of the 25 individual exercise results tests shall be not greater than 11 % (for FFP2) and, in addition, 4 of the 5 arithmetic means for the total inward leakage shall be not greater than 8 % (for FFP2)	Pass			
7.9 Leakage 7.9.2 Penetration of filter material 3 test samples masks tested 'As received', for NaCl (Sodium Chloride) and PO (Paraffin oil), 3min test	Testing shall be done in accordance with 8.11	6% for both PO and NaCl	Pass			
7.12 Carbon dioxide content of the inhalation air 3 test samples, masks tested 'As received'	Testing shall be done in accordance with 8.7.	The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1.0 % (by volume).	Pass			
7.16 Breathing resistance 3 test samples, masks tested 'As received'	Testing shall be done in accordance with 8.9	The breathing resistances shall meet the requirements of, 30l/min – 0.7mbar (inhale) 95l/min – 2.4mbar (inhale) 160l/min – 3.0mbar (exhale)	Pass			
Appendix A - Test Panel Data						
Product Photographs						



Glossary of Terms.

Pass: Complies. Tested by BSI engineers at BSI laboratories

Pass 1: Complies. Witnessed by BSI engineers in manufacturers laboratory.

Pass 2: Complies. Tests carried out by third party lab; results accepted by BSI.

Pass*: Report resulted in uncertainty and states that Compliance is more probable than non-compliance.

Fail: Non-compliance. Product does not meet the requirements of this clause.

Fail*: Report resulted in uncertainty and states that Non-compliance is more probable than compliance.

N/T: Not Tested N/A: Not Applicable AR: As Received

TC: Temperature Conditioned

SW: Simulated Wear FT: Flow Tested

MS: Mechanical strength

MMDF: Manufactures Minimum Design Flow MMDC: Manufactures Minimum Design Condition

Conditions of Issue.

This Test Report is issued subject to the conditions stated in current issue of 'BSI Terms of Service'. The results contained herein apply only to the particular sample(s) tested and to the specific tests carried out, as detailed in this Test Report. The issuing of this Test Report does not indicate any measure of Approval, Certification, Supervision, Control or Surveillance by BSI of any product. No extract, abridgement or abstraction from a Test Report may be published or used to advertise a product without the written consent of BSI, who reserve the absolute right to agree or reject all or any of the details of any items or publicity for which consent may be sought.

Should you wish to speak with BSI in relation to this report, please contact Customer Services on +44 (0)8450 80 9000

BSI Kitemark House Maylands Avenue Hemel Hempstead Hertfordshire HP2 4SQ



Opinions and Interpretations expressed herein are outside the scope of our UKAS accreditation.

Unless otherwise stated, any results not obtained from testing in a BSI laboratory are outside the scope of our UKAS accreditation.



Test Results.

Testing in accordance with BSI COVID-19 filtering face piece technical specification BS EN 149:2001 +A1:2009 Technical testing specification for COVID-19 masks for use by healthcare workers

CLAUSE	REQUIREMENTS	ASSESSMENT
7.7	Practical performance The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard. Where practical performance tests show the apparatus has imperfections related to wearer's acceptance, the test house shall provide full details of those parts of the practical performance tests which revealed these imperfections. Test in accordance with clause 8.4 of the standard. Testing in accordance with BSI COVID-19 filtering face piece technical	Pass
	specification, for masks for use by healthcare workers During the tests the particle filtering half mask shall be subjectively assessed by the wearer and after the test, comments on the following shall be recorded: a) head harness comfort; b) security of fastenings; c) field of vision; d) any other comments reported by the wearer on request.	

Table A: Practical performance

Toet				Comments		
Test candidate	Sample	Head harness comfort	Security of fastenings	Field of vision	Any other comments	Assessment
JB1	1 AR	OK	OK	OK	None	Pass
JS3	2 AR	OK	OK	OK	None	Pass

...making excellence a habit.



Test Results

CLAUSE	REQUIREMENTS		ASSESSMENT

7.9 Leakage

7.9.1 Total inward leakage

The laboratory tests shall indicate that the particle filtering half mask can be used by the wearer to protect with high probability against the potential hazard to be expected. The total inward leakage consists of three components: face seal leakage, exhalation valve leakage (if exhalation valve fitted) and filter penetration.

Test in accordance with clause 8.5 of the standard.

Testing in accordance with BSI COVID-19 filtering face piece technical specification, for masks for use by healthcare workers
Test 3 subjects - If the 3 tests produce results between 6% and 8% mean or individual results over 11%, test 5 subjects

If 5 tests undertaken;

23 of the 25 individual exercise results tests shall be not greater than 11 % (for FFP2) and, in addition, 4 of the 5 arithmetic means for the total inward leakage shall be not greater than 8 % (for FFP2)

Table B: Clause 7.9.1 - Total inward leakage

				Inward Leakage (%)					
Test candidate	Sample	Pre test	А	В	С	D	E	1	
candidate	Sample	condition	Malking	Walking with head side to side	Walking with head up & down	Walking and talking	Walking	Average	Assessment
JS3	3	AR	3.2615	2.0253	3.0112	2.0166	3.2989	2.7227	Pass
JB1	4	AR	2.0291	2.4515	2.6856	4.1372	3.4860	2.9579	Pass
AH1	5	AR	5.0302	6.4092	5.9401	5.5073	6.1333	5.8640	Pass

Pass



Test Results. (Continued)

CLAUSE REQUIREMENTS			ASSESSMENT
---------------------	--	--	------------

7.9.2 Penetration of filter material

Testing in accordance with BSI COVID-19 filtering face piece technical specification, for masks for use by healthcare workers

3 test samples masks tested 'As received', for NaCl (Sodium Chloride) and PO (Paraffin oil), 3 min test. Testing shall be done in accordance with 8.11. 6% limit for both PO and NaCl

Table C: Clause 8.11 - Sodium Chloride penetration test

Sample	Pre-test	Flow through filter (I/min)	Penetra	ation (%)
number	condition	Flow through filter (I/min)	Limit	Actual
8	AR		1	0.0301
9	AR	95	< 6	0.0228
10	AR			0.0652

Table D: Clause 8.11 - Paraffin oil penetration test

Table B. clause 6.11 Taranin on penetration test								
Sample	Pre-test	Flow through filter (I/min)	Penetra	ation (%)				
number	condition	Flow trii ough filter (i/min)	Limit	Actual				
11	AR			0.1815				
12	AR	95	< 6	0.1110				
13	AR			0.0675				

7.12 Carbon dioxide content of inhalation air

The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1.0% (by volume).

Test in accordance with clause 8.7 of the standard.

Table E: Clause 8.7 - Carbon Dioxide content of the inhalation air

Table E. Gladse 6:7 Garbon Bloxide content of the inhalation all						
Cample	Dro tost condition	Dead space CO ₂ (%)				
Sample	Pre-test condition	Limit	Measured			
14	AR	14/	0.45			
15	AR	< 1.0	0.45			
16	AR		0.45			



Pass



Test Results. (Continued)

CLAUSE REQUIREMENTS			ASSESSMENT
---------------------	--	--	------------

7.16 Breathing resistance

Testing in accordance with BSI COVID-19 filtering face piece technical specification, for masks for use by healthcare workers

3 test samples masks tested 'As received'. Test in accordance with clause 8.9 of the standard.

The breathing resistances shall meet the requirements of FFP2; 30l/min – 0.7mbar (inhale), 95l/min – 2.4mbar (inhale), 160l/min – 3.0mbar (exhale)

Table F: Clause 8.9 – Breathing resistance. Inhalation resistance at a continuous flow

Sample	Pre-test	Continuous flow	Inhalation resi	stance (mbar)
Sample	condition	(I/min)	Limit	Measured
17	AR			0.35
18	AR	30	< 0.7	0.34
19	AR			0.39
17	AR			1.13
18	AR	95	< 2.4	1.10
19	AR			1.26

Table G: Clause 8.9 – Breathing resistance. Exhalation resistance at a continuous flow, measured in five orientations with the worst case reported

Cample		Pre-test	Continuous flow	Exhalation resistance (mbar)	
,	Sample	condition	(I/min)	Limit	Measured
	17	AR			1.83
	18	AR	160	< 3.0	1.85
	19	AR			2.05

...making excellence a habit



Appendix A. - Test Panel Data

Test	Facial Dimensions (mm)					Sex
Candidate	Length of face	Width of face	Face depth	Width of mouth	Head Circumference	Sex
JS3	126	134	124	49	600	Male
JB1	114	144	108	59	574	Male
AH1	108	124	130	46	570	Male

Note: All candidates were clean shaven

Product photographs.



Front view



Side view



Inside view

*** End of Report ***

Page 10 of 10

...making excellence a habit.





Introduction

This report has been prepared by Paul Waller and relates to the activity detailed below:

Job/Registration	Details	Client Details	
Job number:	3384906	Huizhou Bowen Manufacturing Ltd.	
Job type:	Testing Samples Submitted	Xinnan 1st Road, Xianan Village	
Start Date:	10/03/2021	Yuanzhou Town, Boluo County	
Test type:	Туре	Huizhou City	
Sample ID:	10196325	Guangdong 516123	
Registration:	CE 729875	China	
Scheme:	Negative pressure RPE	S.IIIId	
Protocol:	PP123	,	'
Scheme Manager:	Nathan Shipley		

The report has been approved for issue by T Wicksey - Senior Test Engineer

Approved For Issue			
20/4	1	Issue Date: 26 April 2021	10

Objectives.

This is an independent Type Test evaluation to BS EN 149:2001+A1:2009. This report covers the gap testing from the BSI COVID-19 filtering face piece technical specification, for COVID-19 masks for use by healthcare workers. See BSI Test Report 3218630 for the BSI COVID-19 filtering face piece technical specification test results.

Product Scope.

Respiratory protective device - Filtering half masks to protect against particles.

Report Summary.

The samples were received on 10 February 2021 and the testing was started on 10 March 2021

The samples submitted complied with the requirements of the test work conducted.





Test Samples.

Sample ID	ER Number	Description	
1 to 37	10196325	Model: Kaze-05 FFP2 NR	

Description of Test	: Samples.	
Sample Description		 18/
Model: Kaze-05 FFP2 NR Valveless	fold flat particle filtering half mask	
KIL		
	4 The	4N
		KNE

...making excellence a habit.



Test Requirements.

BS EN 149:2001 + A1:2009 Respiratory protective devices - Filtering half masks to protect against particles.

	REQUIREMENTS	ASSESSMENT
7	Requirements	-
7.1	General	-
7.2	Nominal values and tolerances	(
7.3	Visual Inspection	Pass (1)
7.4	Packaging	N/T (1)
7.5	Material	Pass
7.6	Cleaning and disinfecting	N/A (2)
7.7	Practical performance	N/T (3)
7.8	Finish of parts	Pass
7.9	Leakage	-
7.9.1	Total inward leakage	Pass (3)
7.9.2	Penetration of filter material	Pass (3)
7.10	Compatibility with skin	Pass
7.11	Flammability	Pass
7.12	Carbon dioxide content of inhalation air	N/T (3)
7.13	Head harness	Pass
7.14	Field of vision	Pass
7.15	Exhalation valves	N/A (4)
7.16	Breathing resistance	Pass (3)
7.17	Clogging	N/A (4)
7.18	Demountable parts	N/A (4)
9	Marking	N/T (1)
10	Information to be supplied by the manufacturer	N/T (1)
Appendix A	A - Test Panel Data	
Product Ph	otographs	

- Packaging, Marking and Information not assessed as requested by BSI Product Certification
- (2) Single use mask
- See also results from BSI COVID-19 filtering face piece technical specification testing, BSI Test Report number 3218630. (3)
- Not a design feature of this product



Glossary of Terms.

Pass: Complies. Tested by BSI engineers at BSI laboratories

Pass 1: Complies. Witnessed by BSI engineers in manufacturers laboratory.

Pass 2: Complies. Tests carried out by third party lab; results accepted by BSI.

Pass*: Report resulted in uncertainty and states that Compliance is more probable than non-compliance.

Fail: Non-compliance. Product does not meet the requirements of this clause.

Fail*: Report resulted in uncertainty and states that Non-compliance is more probable than compliance.

N/T: Not Tested N/A: Not Applicable AR: As Received

TC: Temperature Conditioned

SW: Simulated Wear FT: Flow Tested

MS: Mechanical strength

MMDF: Manufacture r's Minimum Design Flow

Conditions of Issue.

This Test Report is issued subject to the conditions stated in current issue of 'BSI Terms of Service'. The results contained herein apply only to the particular sample(s) tested and to the specific tests carried out, as detailed in this Test Report. The issuing of this Test Report does not indicate any measure of Approval, Certification, Supervision, Control or Surveillance by BSI of any product. No extract, abridgement or abstraction from a Test Report may be published or used to advertise a product without the written consent of BSI, who reserve the absolute right to agree or reject all or any of the details of any items or publicity for which consent may be sought.

Should you wish to speak with BSI in relation to this report, please contact Customer Services on +44 (0)8450 80 9000.

BSI Kitemark House Maylands Avenue Hemel Hempstead Hertfordshire HP2 4SQ



Opinions and Interpretations expressed herein are outside the scope of our UKAS accreditation.

Unless otherwise stated, any results not obtained from testing in a BSI laboratory are outside the scope of our UKAS accreditation.



Test Results

BS EN 149:2001 + A1:2009

Respiratory protective devices - Filtering half masks to protect against particles.

	CLAUSE	REQUIREMENTS		ASSESSMENT
	7.1	General		
		In all tests all samples shall meet the requirements.		-
	7.2	Nominal values and tolerances		
		Unless otherwise specified, the values stated in this European Standard a nominal values. Except for temperature limits, values, which are not state minima, shall be subject to a tolerance of $\pm 5\%$. Unless otherwise specific temperature for testing shall be (16 – 32) °C, and the temperature limits accuracy of \pm 1°C.	ed as maxima or ed, the ambient	LIV.
	7.3	Visual Inspection		
		The visual inspection shall also include the marking and the information s manufacturer.	upplied by the	Pass (1)
	7.5	Material		
		Materials used shall be suitable to withstand handling and wear over the particle filtering half mask is designed to be used.	period for which the	Pass
		After undergoing the conditioning described in clause 8.3.1 of the standar filtering half masks shall have suffered mechanical failure of the facepiece		
		Three particle filtering half masks shall be tested.		Pass
		When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering collapse.	half mask shall not	Pass
		Any material from the filter media released by the air flow through the filt a hazard or nuisance for the wearer.	ter shall not constitute	Pass
		Testing shall be done in accordance with 8.2.		<u> </u>
	7.8	Finish of parts		
		Parts of the device likely to come into contact with the wearer shall have burrs.	no sharp edges or	Pass
		Testing shall be done in accordance with 8.2.		
(1) Marking	and user information were not assessed as requested by BSI Product Certification	fication	1 -'



CLAUSE	REQUIREMENTS		ASSESSMENT
7.9	Leakage		
7.9.1	Total inward leakage		
	The laboratory tests shall indicate that the particle to protect with high probability against the potent	ŭ ,	Pass (1) See Table A

The total inward leakage consists of three components: face seal leakage, exhalation valve leakage (if exhalation valve fitted) and filter penetration.

For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than

25% for FFP1 11% for FFP2 5% for FFP3

and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than $\frac{1}{2}$

22% for FFP1 8% for FFP2 2% for FFP3

Testing shall be done in accordance with 8.5.

Table A: Clause 7.9.1 - Total inward leakage.

				Inv	vard leakage (%).			
Test	Sample	Pre-test condition	А	В	С	D	E	Average
candidate		CONGILION	Walking	Walking with head side to side	Walking with head up & down	Walking and talking	Walking	
RW1	6	AR	1.4684	1.1598	1.3678	1.3983	1.5718	1.3932
LM2	7	AR	1.0715	1.5006	2.5410	1.8796	1.7334	1.7452
JS2	8	TC	1.8161	2.3571	2.7558	1.5499	2.5892	2.2136
KH1	9	TC	0.6444	0.6687	0.7467	0.5452	0.6940	0.6598
BH1	10	TC	2.2431	2.9587	4.1354	2.0157	3.6946	3.0094
RF1	11	TC	1.0241	0.8628	1.4205	0.8537	1.1205	1.0563
LM1	12	TC	5.2988	9.0980	8.3268	5.1433	6.3577	6.8449

(1) **Results for the remaining 'as received' samples are covered** in BSI Test Report number 3218630 for the BSI COVID-19 filtering face piece technical specification testing.



CLAUSE REQUIREMENTS ASSESSMENT

7.9.2 Penetration of filter material

The penetration of the filter of the particle filtering half mask shall meet the requirements of Table 1

A total of 9 samples of particle filtering half masks shall be tested for each aerosol. Testing in accordance with 8.11 using the Penetration test according to EN 13274-7, shall be performed on:

Pass (1) See Tables B and C

3 samples as received,

3 samples after the simulated wearing treatment described in 8.3.1.

Testing in accordance with 8.11 using the Exposure test with a specified mass of test aerosol of 120 mg, and for particle filtering devices claimed to be re-usable additionally the Storage test, according to EN 13274-7, shall be performed:

Pass (1) See Table D and E

for non-re-usable devices on:

3 samples after the test for mechanical strength in accordance with 8.3.3 followed by temperature conditioning in accordance with 8.3.2.

for re-usable devices on:

3 samples after the test for mechanical strength in accordance with 8.3.3 followed by temperature conditioning in accordance with 8.3.2 and followed by one cleaning and disinfecting cycle according to the manufacturer's instruction.

N/A (2)

Table B: Clause 8.11 - Sodium Chloride penetration test.

			Ponotra	tion (%)
Sample	Pre-test condition	Continuous flow (I/min)	Limit	Measured
16	SW	95	6.0	0.2484
17	SW	95	6.0	0.2127
18	SW	95	6.0	0.1049

Table C: Clause 8.11 - Paraffin oil penetration test.

Cample	Pre-test	Continuous flow	Penetra	tion (%)
Sample	condition	(I/min)	Limit	Measured
22	SW	95	6.0	0.1160
23	SW	95	6.0	0.0920
24	SW	95	6.0	0.1280

- (1) **Results for the remaining 'as received' samples are covered** in BSI Test Report number 3218630 for the BSI COVID-19 filtering face piece technical specification testing.
- (2) Not a design feature of this product.



CLAUSE REQUIREMENTS			ASSESSMENT
---------------------	--	--	------------

7.9.2 Penetration of filter material (continued)

Table D: Clause 8.11. Exposure test Sodium Chloride.

	Sample 28 MS TC	Sample 29 MS TC	Sample 30 MS TC	
Flow through filter		95 l/min		
Elapsed time (minutes)	Measured penetration % (Maximum permitted penetration 6.0 %)			
5	0.3145 (1)	0.0776 (1)	0.0670 (1)	
10	0.2622	0.0543	0.0474	
15	0.2278	0.0334	0.0333	
20	0.1946	0.0246	0.0217	
25	0.1678	0.0173	0.0159	
30	0.1415	0.0109	0.0114	
Result	Pass	Pass	Pass	

⁽¹⁾ The reading at which 5 subsequent sampling intervals showed a declining filter penetration. The testing was terminated without the 120mg exposure limit being reached, as permitted by BS EN 13274-7.

...making excellence a habit



CLAUSE REQUIREMENTS ASSESSMEN	CLAUSE F	REQUIREMENTS			ASSESSMENT
-----------------------------------	----------	--------------	--	--	------------

7.9.2 Penetration of filter material (continued)

Table E: Clause 8.11 Paraffin oil exposure test.

	Sample 25 MS TC	Sample 26 MS TC	Sample 27 MS TC
Flow through filter		95 l/min	
Elapsed time (minutes)	(Maxim	Measured penetration % num permitted penetratio	
3	0.5225	0.1815	0.3020
5	0.5140	0.1825	0.3025
10	0.5380	0.1890	0.3090
15	0.5490	0.1960	0.3075
20	0.5600	0.1985	0.3185
25	0.5735	0.1980	0.3135
30	0.5875	0.1970	0.3140
35	0.6110	0.1990	0.3185
40	0.6430	0.1970	0.3195
45	0.6660	0.1970	0.3200
50	0.6895	0.2015	0.3215
55	0.7105	0.2035	0.3215
60	0.7425	0.2030	0.3190
(1)	0.7485	0.2030	0.3180
Result	Pass	Pass	Pass

(1) A loading of 120 mg was achieved after a period of 63 minutes, 10 seconds had elapsed.

...making excellence a habit.



CLAUSE	REQUIREMENTS				ASSESSMENT
7.10	Compatibility wit	h skin			
		come into contact with the wea l ny other adverse effect to healt		be known to be likely to	Pass
	Testing shall be dor	ne in accordance with 8.4 and 8	.5.		
7.11	Flammability				
	The material used s flammable nature.	shall not present a danger for th	e wearer and sha	ll not be of a highly	
		article filtering half mask shall n noval from the flame.	ot burn or not cor	ntinue to burn for more than	Pass See Table F
	The particle filtering	g half mask does not have to be	usable after the	test.	
	Testing shall be dor	ne in accordance with 8.6.			
	Table F: Clause 8.6	6 – Flammability.			
	Sample	Area exposed		Comments	
	34 AR	Filter material, earlo	ор	Did not ignite	
			7		T

7.13 Head harness

35 AR

36 TC

37 TC

The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.

Noseband.

Filter material, earloop

Noseband.

The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.

Testing shall be done in accordance with 8.4 and 8.5.

7.14 Field of vision

The field of vision is acceptable if determined so in practical performance tests.

Testing shall be done in accordance with 8.4.

Pass

Pass

Did not ignite

Did not ignite

Did not ignite



CLAUSE REQUIREMENTS ASSESSMENT	CLAUSE REQUIREMENTS			ASSESSMENT
------------------------------------	---------------------	--	--	------------

7.16 Breathing resistance

The breathing resistances apply to valved and valveless particle filtering half masks and shall meet the requirements of Table 2.

Testing shall be done in accordance with 8.9.

A total of 9 valveless particle filtering half masks shall be tested:

3 as received, 3 after temperature conditioning in accordance with 8.3.2 and 3 after the test for simulated wearing in accordance with 8.3.1.

See Tables G, I and I

Testing shall be done in accordance with 8.9

A total of 12 valved particle filtering half masks shall be tested: 3 as received, 3 after temperature conditioning in accordance with 8.3.2, 3 after the test for simulated wearing in accordance with 8.3.1, and 3 after the flow conditioning in accordance with 8.3.4.

N/A(2)

Pass (1)

Testing shall be done in accordance with 8.9.

Table G: Clause 8.9 - Breathing resistance. Inhalation resistance at a continuous flow.

Sample	Pre-test condition	Flow (I/min)	Limit (mbar)	Measured (mbar)
16	SW	30	0.7	0.45
17	SW	30	0.7	0.45
18	SW	30	0.7	0.43
31	TC	30	0.7	0.35
32	TC	30	0.7	0.33
33	TC	30	0.7	0.35

Table H: Clause 8.9 - Breathing resistance. Inhalation resistance at a continuous flow.

	0			
Sample	Pre-test condition	Flow (I/min)	Limit (mbar)	Measured (mbar)
16	SW	95	2.4	1.46
17	SW	95	2.4	1.42
18	SW	95	2.4	1.46
31	TC	95	2.4	1.20
32	TC	95	2.4	1.19
33	TC	95	2.4	1.22

Results for the remaining 'as received' samples are covered in BSI Test Report number 3218630 for the BSI COVID filtering face piece technical specification testing.

Not a design feature of this product.



CLAUSE REQUIREMENTS		ASSESSMENT

7.16 Breathing resistance (continued)


Table I: Clause 8.9 – Breathing resistance. Exhalation resistance at a continuous flow, measured in five orientations with the highest value recorded.

Sample	Pre-test condition	Flow (I/min)	Limit (mbar)	Measured (mbar)
16	SW	160	3.0	2.32
17	SW	160	3.0	2.31
18	SW	160	3.0	2.32
31	TC	160	3.0	2.07
32	TC	160	3.0	2.03
33	TC	160	3.0	2.06

Appendix A. – Test Panel Data

Test	Facial Dimensions (mm)					
Candidate	Length of face	Width of face	Face depth	Width of mouth	Head Circumference	Gender
RW1	110	145	125	60	585	Male
LM2	110	148	125	44	589	Male
JS2	126	142	125	57	575	Male
KH1	112	142	115	60	585	Male
BH1	120	126	120	58	565	Male
RF1	104	122	121	55	549	Male
LM1	111	138	96	54	545	Female

Note: All candidates were clean shaven







Product photographs.



Front view



Side view



Inside view

*** End of Report ***

...making excellence a habit.



Report No.: S20071602001E page 1 of 12

Test Report

Applicant: Huizhou Bowen Manufacturing Limited

Address: Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou

City, Guangdong Province, P.R.China

The following sample(s) was/were submitted and identified on behalf of the client as:

Product name: Protective Respirator

Model: NON-STERILE FOLD MASK

Trade mark: KAZE

Manufacturer: Huizhou Bowen Manufacturing Limited

Address: Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou

City, Guangdong Province, P.R.China

Claim level: FFP2
Sample quantity: 120 Pcs

Sample Received

Jul. 17, 2020

Testing Period: Jul. 17, 2020~ Jul. 21, 2020

Test Requirement:

According to the requirement of the client, the test item(s) of the sample is according to the standard EN149:2001+A1:2009.

Test Result(s): Please refer to the following page(s)

Test Method: Please refer to the following page(s)

Approved by:

Reviewed by:

Date: 2020-07-22

Shenzhen NTEK Testing Technology Co., Ltd. | Address: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R.China. | Tel: +86-755-36995508 | Fax: +86-755-36995505 http://www.ntek.org.cn



page 2 of 12

Summary of assessment*

Clause	Assessment
7.3 Visual inspection	NRq
7.4 Packaging	Pass
7.5 Material	Pass
7.6 Cleaning and disinfecting	N.A.
7.7 Practical performance	Pass
7.8 Finish of parts	Pass
7.9.1 Total inward leakage	Pass
7.9.2 Penetration of filter material	Pass
7.10 Compatibility with skin	Pass
7.11 Flammability	Pass
7.12 Carbon dioxide content of the inhalation air	Pass
7.13 Head harness	Pass
7.14 Field of vision	Pass
7.15 Exhalation valve(s)	N.A.
7.16 Breathing resistance	Pass
7.17 Clogging	N.A.
7.18 Demountable parts	Pass

Key

Pass	Requirement satisfied.
NRq	The clauses were not required.
Fail	Requirement not satisfied. Refer to the "Result details" section for more information.
N.A.	Assessment not carried out.

^{*} Assessment relates only to those specimens which were tested and are the subject of this report.



page 3 of 12

Test Result

Respiratory Protective Devices — Filtering Half Masks to Protect against Particles — Requirements, Testing, Marking

(EN 149:2001+A1:2009)

Clause 7.3 Visual inspection

Test Requirement	Results	Comment
Marking and the information supplied by the manufacturer, requirements refer to clause 9 and clause 10.	The clauses were not required.	NRq

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged		
in such a way that they are protected against mechanical	Comply	Pass
damage and contamination before use.		

Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear		
over the period for which the particle filtering half mask is	Comply	Pass
designed to be used.		
After undergoing the conditioning described in 8.3.1 none of the		
particle filtering half masks shall have suffered mechanical	Comply	Pass
failure of the face piece or straps.		
When conditioned in accordance with 8.3.1 and 8.3.2 the	Comply	Pass
particle filtering half mask shall not collapse.	Comply	Pass
Any material from the filter media released by the air flow	17.7	
through the filter shall not constitute a hazard or nuisance for	Comply	Pass
the wearer.		



Report No.: S20071602001E page 4 of 12

Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable,		
the materials used shall withstand the cleaning and		
disinfecting agents and procedures to be specified by the manufacturer. With reference to 7,9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Assessment not carried out.	N.A.

Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
A Control of the Cont	Sample 11#~12#:	
General:		
a) head harness comfort		
b) security of fastenings	No imperfections	
c) field of vision		
d) any other comments reported by the wearer on request.		
Walking Test:		
The subjects wearing normal working clothes and wearing		
the particle filtering half mask shall walk at a regular rate of 6	No imperfections	
km/h on a level course. The test shall be continuous, without	THE IIII POLICE AND III	
removal of the particle filtering half mask, for a period of 10		Pass
min.		
Work Simulation Test:		\ <u>\</u>
a) walking on the level with headroom of (1.3 \pm 0.2)m for 5min		
b) crawling on the level with headroom of (0.7 \pm 0.05)m for		
5min		
c) filling a small basket (see Figure 1, approximate volume =	No imperfections	
8 L) with chippings or other suitable material from a hopper	44/	4
which stands 1.5 m high and has an opening at the bottom to		
allow the contents to be shovelled out and a further opening		
at the top where the basket full of chippings is returned.		



Report No.: S20071602001E page 5 of 12

Clause 7.8 Finish of Parts

EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer	No sharp edges or	Door
shall have no sharp edges or burrs.	burrs	Pass

Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009 Clause 8.5)

Test Requirement	Results	Comment
For particle filtering half masks fitted in accordance with the		
manufacturer's information, at least 46 out of the 50 individual		
exercise results (i.e. 10 subjects x 5 exercises) for total inward		
leakage shall be not greater than:		
25% for FFP1		
11% for FFP2	Detail refer to	Pass
5% for FFP3	Appendix 1	Pass
and, in addition, at least 8 out of the 10 individual wearer arithmetic		
means for the total inward leakage shall be not greater than:		
22% for FFP1		
8% for FFP2		
2% for FFP3		

Appendix 1: Summarization of Test Data

Appendi	x I. Suniii	iai izalioni oi	Test Data			Λ		
			Normal	Head	Head	Speak	Normal	Mean
Subject	Sample	Condition	Breathing	Side/Side	Up/Down	Loudly	Breathing	
			(%)	(%)	(%)	(%)	(%)	(%)
Zhai	1#	A.R.	2.3	2.8	2.8	3.1	2.6	2.72
Wu	2#	A.R.	5.4	5.2	6.3	8.8	7.4	6.62
Zhang	3#	A.R.	3.3	3.9	3.7	4.2	3.2	3.66
Yang	4#	A.R.	4.7	5.3	5.3	6.1	4.9	5.26
Yan	5#	A.R.	2.9	3.4	3.5	3.8	3.0	3.32
Chen	6#	T.C.	40	4.5	4.4	5.2	4.6	4.54
Lei	7#	T.C.	5.8	6.3	6.1	6.7	6.0	6.18
He	8#	T.C.	4.7	5.6	5.0	6.0	5.5	5.36
Zhong	9#	T.C.	5.1	5.7	5.6	6.2	6.1	5.74
Li	10#	T.C.	3.6	4.4	4.0	4.8	3.9	4.14



Report No.: S20071602001E page 6 of 12

Facial Dimension:

Subject	Length of Face	Width of Face	Depth of Face	Width of Mouth
Guojoot	(mm)	(mm)	(mm)	(mm)
Zhai	135	165	125	53
Wu	112	172	118	55
Zhang	120	175	115	57
Yang	125	165	120	55
Yan	104	163	115	52
Chen	111	137	121	53
Lei	112	138	119	54
He	114	127	121	51
Zhong	105	135	103	52
Li	109	123	109	60

Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

	Test Requirement		Results	Comment
The penetration of	the filter of the particle filt	ering half mask shall		1
meet the requirem	ents of the following table			
	Maximum penetrati	on of test aerosol		
	Sodium chloride test	Paraffin oil test		
Classification	95 L/min	95 L/min	Detail refer to	
	%	%	Appendix 2	Pass
	max.	max.		
FFP1	20	20		
FFP2	6	6		\
FFP3	1	1		



page 7 of 12

Appendix 2: Summarization of Test Data

Penetration of filter material

			_	()	
		Sample	Penetration	on (%)	Assessment
Aerosol	Condition	No.	Average in 30s	Max. during	
			after 3 min	exposure	
		13#	1.2		
	A.R.	14#	1.3	Î	
.15		15#	1.2	1	
		22#	1.1	1	
Sodium chloride test	S.W.	23#	1.2	/	
		24#	1.2	/	
		25#	1	2.0	
	M.S. + T.C.	26#	////	2.2	
		27#	1	2.3	
	,	16#	2.7	1	Pass
	A.R.	17#	3.1	/	
		18#	2.6	/	
		19#	2.9	/	
Paraffin oil test	S.W.	20#	2.6	1	
1001		21#	2.9		
		28#	1	5.2	
	M.S. + T.C.	29#	1	5.3	
		30#	1	5.2	
	Flo	w conditionin	g: 95.0 L/min		

Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall	No irritation or any	
not be known to be likely to cause irritation or any other adverse	other adverse effect	Pass
effect to health.	to health	



page 8 of 12

Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and		
shall not be of highly flammable nature when tested, the particle	Detail refer to	Pass
filtering half mask shall not burn or not to continue on burn for	Appendix 3	Fass
more than 5 s after removal from the flame.		

Appendix 3: Summarization of Test Data

Flammability

Condition	Sample No.	Result	Assessment
	31#	Flammable, burn for no	
A.R.	31#	more than 5 s	
	32#	Nonflammable	Pass
TC 4	33#	Nonflammable	/
T.C.	34#	Nonflammable	

Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not exceed an average of 1.0 % (by volume)	Detail refer to Appendix 4	Pass

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Result		Assessment
	35#	0.19%	Magazzalia	
A.R.	36#	0.23%	Mean value 0.22%	Pass
	37#	0.23%	0.22%	



page 9 of 12

Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in	Comply	Pass
position and be capable of maintaining total inward leakage requirements for the device.	Comply	

Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical	Comply	Pass
performance		

Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Assessment not carried out.	
b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Assessment not carried out.	N.A.
c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Assessment not carried out.	
(d) When the exhalation valve housing is attached to the face blank, it shall withstand axially a tensile force of 10N applied for 10 s.	Assessment not carried out.	1



page 10 of 12

Clause 7.16 Breathing Resistance EN 149:2001+A1:2009, Clause 8.9)

	Test Requi	Results	Comment		
The penetration of the	filter of the pa				
meet the requirements					
1	Maximum pe	rmitted resista	ance (mbar)		
Classification	Inhala	ition	Exhalation	Detail refer to	
	30 L/min	95 L/min	160 L/min	Appendix 5	Pass
FFP1	0.6	2.1	3.0		
FFP2	0.7	2.4			
FFP3	1.0	3.0			

Appendix 5: Summarization of Test Data

	N,	Inhala	ition	Exhalation resistance(mbar)					
Specimen	Condition	At 30	At 95	At 160 L/min					
		L/min	L/min	Α	В	С	D	E	
38#		0.5	2.1	2.4	2.4	2.4	2.4	2.4	
39#	A.R.	0.5	2.2	2.3	2.3	2.3	2.3	2.3	
40#	0.5		2.1	2.5	2.5	2.5	2.5	2.5	
41#		0.5	2.2	2.5	2.6	2.5	2.5	2.5	
42#	S.W.	0.5	2.2	2.5	2.6	2.6	2.5	2.5	
43#		0.5	2.2	2.5	2.5	2.5	2.5	2.5	
44#		0.5	2.3	2.5	2.5	2.5	2.5	2.5	
45#	T.C.	0.5	2.3	2.5	2.5	2.5	2.5	2.5	
46#		0.5	2.3	2.5	2.5	2.5	2.5	2.5	
1		1	/	/	1	/	/	/	
/	F.C.	/	/	/	/	/	/	/	
/		/	/	/	/	/	/	/	

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

	Test Requirement		Results	Comment
Claus Valve After clogging the inh mbar, FFP2: 5 mbar, exhalation resista Valvele After clogging the in exceed: FFP1: 3 mb	Assessment not carried out.	N.A.		
	Test Requirement	<i>*</i>	Results	Comment
All types (valved and v		er material ering half masks claimed meet the requirements.		1
	Maximum penetrati	ion of test aerosol		
	Sodium chloride	Paraffin oil test	Assessment	
Classification	test 95 L/min	95 L/min	not carried	N.A.
Classification	test 95 L/min %	95 L/min %	not carried out.	N.A.
Classification				N.A.
Classification FFP1	%	%		N.A.
	% max.	% max.		N.A.
FFP1	% max. 20	% max. 20		N.A.

page 11 of 12

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured, where possible by hand	Comply	Pass





page 12 of 12

Sample photo(s):



Fig.1



Fig.2

****End of Report****

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of NTEK, this report can't be reproduced except in full.



Number: GZHT02329728

Report Ref:	GZHT02329728		
Date Received:	Aug 21, 2020	Date Issued:	Sep 02, 2020

Company Name: HUIZHOU BOWEN MANUFACTURING LIMITED

Address: XINNAN 1ST ROAD, XIANAN VILLAGE YUANZHOU TOWN, BOLUO COUNTY

YUANZHOU TOWN, BOLUO COUNTY HUIZHOU CITY, GUANGDONG PROVINCE

P.R.CHINA

Contact Name: 廖敏

The Following Sample Was Subm	itted And Identified By/On Behalf Of The Applicant As:	
End Uses	Non-Sterile Medical Face Mask	
Ratings	Type I	
Sample Name	FFP2 NR Protective Respirator	
No. Of Sample	One(20 pieces)	
Size	15.5cmX10.5cm	
Colour	White	
Standard	EN 14683:2019+AC:2019	
Brand Name	KAŻE	
Buyer	NCK LIMITED (博文)	
Manufacturer	Huizhou Bowen Manufacturing Limited	
Date received/ Test Started	Aug 21, 2020	
Ref	Type No.: KAZE-01	
	Lot No.: 2020-08	

Test was conducted on specific items, at our client's request.

Prepared And Checked By:

For Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Lin Lin

General Manager

QIN / pennytao



Page 1 Of 4

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

深圳天祥质量技术服务有限公司广州分公司

Room 02, 1-8/F & Room 01, E101/E201/E301/E401/E501/E601/E201/E901, No.7-2, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, Cinna中国广州经济技术开发区科学城彩频路 7 号之二第 1—8 层 02 房。

E201、E301、E401、E501、E601、E701、E801

Tel: +86 20 8213 9001 Fax: +86 20 8208 9909 Postcode: 510663

Hengyun Building, 235 Kaifa Ave., Guangzhou


Ropromic & Technological Development District, Guangzhou, China

上 中国广州经济技开发区开发大道 235 号恒运大厦 3 楼

: +86 20 8396 6868 Fax: +86 20 8222 8169 Postcode: 510730



Number: GZHT02329728



Prepared And Checked By: For Intertek Testing Services Shenzhen Ltd. Guangzhou Branch



Lin Lin General Manager

QIN / pennytao



Intertek Testing Services Stienzhen Ltd. Guangzhou Branch

深圳天祥质量技术服务有限公司广州分公司

Room 02, 1-8/F & Room 01, E101/E201/E301/E401/E501/E601/F701/F701, No.7-2, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China 中国广州经济技术开发区科学城彩频路7号之二第1-8层02房

E201、E301、E401、E501、E601、E701、E801 Tel: +86 20 8213 9001 Fax: +86 20 8208 9909 Postcode: 510663

Hengyun Building, 235 Kaifa Ave., Guangzhou

conomic & Technological Development District, Guangzhou, China

中国广州经济技开发区开发大道 235 号恒运大厦 3 楼

+86 20 8396 6868 Fax: +86 20 8222 8169 Postcode: 510730



Number: GZHT02329728

Summary of testing:


With reference to following standard:

EN 14683:2019+AC:2019 Medical face masks – Requirements and test methods Type I

Materials Used in The Submitted Sample Were Found To Comply With The Type I Requirements of EN 14683:2019+AC:2019 with respect to Bacterial Filtration Efficiency test.

the the the

Prepared And Checked By: For Intertek Testing Services Shenzhen Ltd. Guangzhou Branch



Lin Lin General Manager

QIN / pennytao



Page 3 Of 4

Intertek Testing Services Stienzhen Ltd. Guangzhou Branch

深圳天祥质量技术服务有限公司广州分公司

Room 02, 1-8/F & Room 01, E101/E201/E301/E401/E501/E601/E701/E301, No.7-2, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China 中国广州经济技术开发区科学城彩频路 7 号之二第 1—8 层 02 房 01 房 101、

E201、E301、E401、E501、E601、E701、E801 Tel: +86 20 8213 9001 Fax: +86 20 8208 9909 Postcode: 510663 Hengyun Building, 235 Kaifa Ave., Guangzhou

中国广州经济技开发区开发大道 235 号恒运大厦 3 楼

: +86 20 8396 6868 Fax: +86 20 8222 8169 Postcode: 510730



Tests Conducted (As Requested By The Applicant)

Number: GZHT02329728

1 Bacterial Filtration Efficiency (BFE)

As Per EN 14683:2019+AC:2019 Medical face masks - Requirements And Test Methods Annex B.

			D (01)			<u>Performance</u>
Tost Itom			Results (%)		1	Requirement for
<u>Test Item</u>	Specimen	Specimen	Specimen	Specimen	Specimen	<u>Medical Face</u>
	(1)	(2)	(3)	(4)	(5)	<u> Mask (%)</u>
Bacterial	>99.9	>99.9	>99.9	>99.9	>99.9	
Filtration				_		Type I: ≥95
Efficiency						1,700 1. = 70
(BFE)						

Remarks:

- 1. Biological Aerosol: Staphylococcus aureus (ATCC 6538).
- 2. Testing side: Inside of the test specimen was facing towards the challenge aerosol.
- Test area: 78 cm²
 Flow rate: 28.3 L/min
- 5. The average plate count results of the positive controls: 2.4*10³ CFU
- 6. The average plate count results of the negative controls: < 1 CFU
- 7. CFU = Colony Forming Unit

Remark: This test item was conducted in Caipin Road, Guangzhou Science City, GETDD, Guangzhou, Guangdong.

End of Report

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. No copy of the test report(except for full text copy) shall be made without the written approval by Intertek.

QIN / pennytao

Page 4 Of 4

Intertek Testing Services Stienzhen Ltd. Guangzhou Branch 深圳天祥质量技术服务有限公司广州分公司

Room 02, 1-8/F & Room 01, E101/E201/E301/E401/E501/E601/F791/E901, No.7-2, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China 中国广州经济技术开发区科学城彩频路 7 号之二第 1—8 层 02 房 切 房 101、

#3/10 + 10 HOW TO 1: +

He: +86 20 8396 6868 Fax: +86 20 8222 8169 Postcode: 510730

promic & Technological Development District, Guangzhou, China

Hengyun Building, 235 Kaifa Ave., Guangzhou

中国广州经济技开发区开发大道 235 号恒运大厦 3 楼

E201、E301、E401、E501、E601、E701、E801 Tel: +86 20 8213 9001 Fax: +86 20 8208 9909 Postcode: 510663

(10)

















国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验报告 Test Report


第1页 共6页

	1115 #	1 2 0 2 1 4 9 1 1	Page 1 of 6
	委托单位/地址 Applicant	惠州博文制造有限公司 送样人: Huizhou Bowen Manufacturing Limited Contact 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China	
a Silent Silent	生产单位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Guangdong Province, P.R.China	, Huizhou City,
尸提供信息及要求 Information Drovided by	样品信息 Information of Submitted Sample	样品名称: KN95防护口罩 商标: KAZE Sample Name KN95 Protective Respirator Trademark 样品总数: 45个 Sample Count 45Pieces 号型规格: 折疊型口罩 颜色: / Colour 5量等级:	
	, ,, – , ,	Quality Grade Safety / Category 产品款号或货号: 2020-07 Style No. or Order No. GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory propowered air-purifying particle respirator	tection-Non-
	样品描述 est Part escription	1# 白色口罩White Mask	Res.
1	检验性质 Fest Type	委托检验 Commission Test Kanage of Submission And Submission	2080-07-28
	检验日期 Test Date 执行标准 st Standards	2020-07-23 型 To 2020-07-23 NOTE: The second of the sec	川章
С	检验结论 onclusion	检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	1
	备注 Remarks	客户要求过滤效率测试初始过滤效率,并按照GB 2626-2019标准判定。 As per client's request that the Filtration Efficiency is required to test initial filtration efficiency, and judged according to the standard GB 2626-2019.	

批准: Approver



审核: Checker



编制: Editor

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第2页 共6页

TTTS-WT2021	4911						Page 2 of 6
检测项目	;	项目描述	单位	标准值	实测值	评价	执行标准/备注
Test Items		scription	Unit	Standard	Results	Conclu	
		-	ļ	Requirement		sions	Remarks
1# 白色口	罩White Ma	sk				•	
					未预处理样品		
					Samples Without		
			\ \		Pretreatment: 1: 191		
		呼气阻力			2: 208		, ,
		piratory esistance	Pa	€210	预处理样品		
	I Ne	esistance			Samples With		
					Pretreatment:		
呼吸阻力					1: 180 2: 187	符合	
Respirator					未预处理样品	Pass	GB 2626-2019
Resistance	e				Samples Without		
				$\Lambda \sim$	Pretreatment:		
	I	吸气阻力			1: 209		
	Ins	spiratory	Pa	≤210	2: 210 预处理样品		
	Re	esistance	/ -'		Samples With		
					Pretreatment:		
					1: 188		
		续燃时间			2: 191		
可燃性	Δf	狭然时刊 terflame	S	≤ 5	0	符合	GB 2626-2019
Flammabili [.]	ty	Time				Pass	GD 2020 2010
	AV			按标准要求			
		样品表面	1 -	As per			
4	Suri	Eace of The Sample		standard requirement	+		
		башртс		requirement			
		一材料和结构		按标准要求		1	
		mponent	,	As per			
		erial and	/	standard requirement	+		
	Con	struction		requirement			
外观检查	部件	经过温度湿				1	
Appearance		· 预处理后		按标准要求		符合	GB 2626-2019
Inspection	lhe	components	,	As per		Pass	05 2020 2010
1		fter the operature		standard requirement	T		
		humidity		requirement			
	pre	etreatment	V]	
		和制造商所	_	+÷+=: \/->	Ť		*
		k的各种信息 ibel and		按标准要求 As per			
		arious	/	standard	+		
		Cormation		requirement			
		ovided by		14/	441		447
	man	ufacturer			4.7		4.7

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第3页 共6页

TTTS-WT20214911				Y		Page 3 of 6
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
		+		初始过滤效率 Initial Filtration Efficiency 未预处理样品 Samples Without Pretreatment: 1: 99.79 2: 99.80 3: 99.81 4: 99.85 5: 99.85	>	
过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥95. 0	6: 99.85 7: 99.81 8: 99.79 9: 99.82 10: 99.80 11: 99.79 12: 99.82 13: 99.83 14: 99.81 15: 99.83 预处理样品	符合 Pass	GB 2626-2019
		7	16	Samples With Pretreatment: 1: 99.75 2: 99.72 3: 99.73 4: 99.73 5: 99.70		
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验报告 Test Report

第4页 共6页 Page 4 of 6

TTTS-WT20214911

1115-W120214911						Page 4 of 6
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
头带 Head Harness		1	呼吸器的每条头带、形扣及其他调节部件在承受 10N,持续10s的拉力时,不应出现滑脱或断裂 Each head harness, buckle and other adjustment components of the respirator should not have slippage or breaking for 10s under 10N loading.	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019

表中"+"表示符合标准要求, "X"表示不符合标准要求。

⁺ Meet the standard requirements, X Not Meet the standard requirements.

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第5页 共6页 Page 5 of 6

TTTS-WT20214911

样 밂 Sample



















天纺标检测认证股份有阻公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tian

国家针织产品质量监督检验中心

POINTS FOR ATTENTION

第6页 共6页 Page 6 of 6

1.检验报告无"检验专用章"无效。

Report is invalid without stamp of "special seal for the test report".

2.复制报告未重新加盖"检验专用章"无效。

Copy report is invalid without re-stamp of "special seal for the test report".

3.报告无编写、审核、批准人签字无效。

Report is invalid without collective signatures by editor, checker and approver.

4.检验报告涂改无效。

Report is invalid if altered.

5.检验报告或复制报告未加盖骑缝章无效(报告页数多于1页时)。

Report and copy report is invalid without stamp of "Paging Seal" (When the page number more than 1).

6.委托检验仅对来样负责,不承担其他连带责任。

Unless otherwise stated the results shown in this report refer only the sample(s) tested.

7.对于检验结果若有异议,应于收到报告之日起十五日内向本机构提出,逾期不予受理。

Objection should be issued in 15 days upon receiving the report, overdue opinion is inadmissible.

8.未经本机构书面批准,部分复制报告无效。

Part copy report is invalid without the approval of the written documents of the testing organization.

--报告结束 End of report----

注意事项以中文为准The English edition is for reference only

天纺标集团检测单位与地址 Tianfangbiao Groups Others Testing Location

天纺标检测认证股份有限公司

Tianfangbiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津)

China National Clothing Quality Inspection & Supervision Center (Tianjin)

国家针织产品质量监督检验中心

China National Knitted Product Quality Supervision Testing Center

地址:天津市南开区鹊桥路25号

Address: No.25, Quegiao Road, Nankai District, Tianjin, China



扫码下载电子报告



扫码关注天纺标

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验报告 Test Report


第1页 共7页

	1113 W	120207761	第1页 共7页
þ	委托单位/地址 Applicant	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China 送样人: Contact ### Contact ### Contact ### Contact ### Limited ### Contact ### Contact ### Limited ### Limited	
女 by Client	生产单位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Guangdong Province, P.R.China	Huizhou City,
广提供信息及要求 Information brovided by	样品信息 Information of Submitted Sample	样品名称: KN95防护口罩 商标: KAZE Sample Name KN95 Protective Respirator Trademark 样品总数: 50个 Sample Count 50Pieces	
	Test Standards	Order No. GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory prote powered air-purifying particle respirator 1# 浅灰色口罩 Light Grey Mask	ection-Non-
T	样品描述 est Part escription	2# 酒红色口罩 Wine Mask 3# 粉色口罩 Pink Mask 4# 浅蓝色口罩 Light Blue Mask 5# 玫红色口罩 Rose Mask 6# 橙色口罩 Orange Mask	W. G.
Т	检验性质 est Type 检验日期	委托检验 Commission Test Submission #AB接收日期 Date of Submission 2020-07-13 Date dayCheckan,	e di
Tes	Mest Date 执行标准 st Standards 检验结论 onclusion	2020-07-13 到 To 2020-07-13 DNM (e) See next page(s) 检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	H章
	备注 Remarks	/	4 (

批准: Approver



审核: Checker



编制: Editor

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第2页 共7页

<u>T</u>	TTS-WT20207761				•		Page 2 of 7
	检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	1# 浅灰色口罩 L	ight Grey Mask		.6,	.6	,	.6.
	4	样品表面 Surface of The Sample	1	按标准要求 As per standard requirement			
		部件材料和结构 Component Material and Construction	/	按标准要求 As per standard requirement	+		
	外观检查 Appearance Inspection	部件经过温度湿 度预处理后 The components after the temperature and humidity	S	按标准要求 As per standard requirement		符合 Pass	GB 2626-2019
		pretreatment 标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		
	2# 酒红色口罩 W	ine Mask					

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第3页 共7页

TTTT TTTO						和50人人1人
TTTS-WT20207761						Page 3 of 7
检测项目 Test Items	项目描述 Description	単位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
过滤效率 Filtration Efficiency	氯化钠颗粒物 NaCl Particle	%	≥95. 0	初始过滤效率 Initial Filtration Efficiency: 未预处理样品 Samples Without Pretreatment 1: 99.37 2: 99.43 3: 99.38 4: 99.41 5: 99.47 6: 99.49 7: 99.38 8: 99.40 9: 99.33 10: 99.34	符合 Pass	GB 2626-2019
(KN95)				11: 99.40 12: 99.33 13: 99.35 14: 99.35 15: 99.40 预处理样品 Samples With Pretreatment: 1: 95.99 2: 96.24 3: 96.52 4: 96.24 5: 95.78		
3# 粉色口罩 Pin	k Mask	V				

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

						第4页 共7页
TTTS-WT20207761						Page 4 of 7
检测项目	项目描述	单位	标准值	实测值	评价	执行标准/备注
Test Items	Description	Unit	Standard	Results	Conclu	Test Method/
			Requirement	未预处理样品	sions	Remarks
				Samples Without		
				Pretreatment:		
	呼气阻力			1: 131		
	Expiratory	Pa	≤210	2: 135		
	Resistance	1 4	210	预处理样品		
		N	1	Samples With		
v				Pretreatment: 1: 114		*
呼吸阻力				2: 120	符合	
Respiratory				未预处理样品	Pass	GB 2626-2019
Resistance				Samples Without	rass	
				Pretreatment:		
4	吸气阻力			1: 139		
	Inspiratory	Pa	€210	2: 143		1
	Resistance	1 a	210	预处理样品		
	11001010101	1		Samples With		
				Pretreatment: 1: 127		\
				2: 121		
4# 浅蓝色口罩 L	ight Blue Mask			2. 121	1	-
	下方视野		> 0.5	21		
视野	View Blow		≥35	61	符合	GB 2890-2009
View	双目视野	%	≥65	>65	Pass	GD 2090 2009
	Binocular View			, , , ,		
5# 玫红色口罩 R	Rose Mask					
			呼吸器的每条头			
		\ <u>-</u> '	带、带扣及其他			\
			调节部件在承受			
			10N, 持续10s			
			的拉力时,不应 出现滑脱或断裂			
			Each head			
			harness,	10N负荷持续10秒,头带未		
N. HII			buckle and	出现滑脱、断裂	<i>kk</i>	197
头带 Head Harness	/	/ ,	other	The head harness have no slippage or	符合 Pass	GB 2626-2019
neau narness			adjustment	brooking for 10s under	rass	
		1 1	components of	10N loading		
		1-	the			\-\'
			respirator should not			
			have slippage			
			or breaking			
			for 10s under			
			10N loading.			
6# 橙色口罩 0ra	ange Mask		18	$A \sim$		

















天纺标检测认证股份有阻公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第5页 共7页

1115-W1ZUZU1161						Page 5 of 1
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
可燃性 Flammability	续燃时间 Afterflame Time	S	€5	0	符合 Pass	GB 2626-2019

表中"+"表示符合标准要求,"X"表示不符合标准要求。

 $^{^{+}}$ Meet the standard requirements, $\ensuremath{\mathrm{X}}$ Not Meet the standard requirements.





TTTS-WT20207761















天纺标检测认证股份有限公司 TianFangBiao Standardization Certification & Testing Co.,Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第6页 共7页

Page 6 of 7

样 品 Sample



















天纺标检测认证股份有限公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tian)

国家针织产品质量监督检验中心

POINTS FOR ATTENTION

第7页 共7页 Page 7 of 7

1.检验报告无"检验专用章"无效。

Report is invalid without stamp of "special seal for the test report".

2.复制报告未重新加盖"检验专用章"无效。

Copy report is invalid without re-stamp of "special seal for the test report".

3.报告无编写、审核、批准人签字无效。

Report is invalid without collective signatures by editor, checker and approver.

4.检验报告涂改无效。

Report is invalid if altered.

5.检验报告或复制报告未加盖骑缝章无效(报告页数多于1页时)。

Report and copy report is invalid without stamp of "Paging Seal" (When the page number more than 1).

6.委托检验仅对来样负责,不承担其他连带责任。

Unless otherwise stated the results shown in this report refer only the sample(s) tested.

7.对于检验结果若有异议,应于收到报告之日起十五日内向本机构提出,逾期不予受理。

Objection should be issued in 15 days upon receiving the report, overdue opinion is inadmissible.

8.未经本机构书面批准,部分复制报告无效。

Part copy report is invalid without the approval of the written documents of the testing organization.

--报告结束 End of report----

注意事项以中文为准The English edition is for reference only

天纺标集团检测单位与地址 Tianfangbiao Groups Others Testing Location

天纺标检测认证股份有限公司

Tianfangbiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津)

China National Clothing Quality Inspection & Supervision Center (Tianjin)

国家针织产品质量监督检验中心

China National Knitted Product Quality Supervision Testing Center

地址:天津市南开区鹊桥路25号

Address: No.25, Quegiao Road, Nankai District, Tianjin, China



扫码下载电子报告



扫码关注天纺标

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验报告 Test Report


第1页 共7页 Page 1 of 7

	1110 "	120214901	Page 1	of 7
<i>P</i>	委托单位/地址 Applicant	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China		
a 与 a p c l i ent	生产单位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Guangdong Province, P.R.China	Huizhou	City,
尸提供信息及要求 Information Drovided by	样品信息 Information of Submitted	样品名称: KN95防护口罩 商标: KAZE Sample Name KN95 Protective Respirator Trademark 样品总数: 45个 Sample Count 45Pieces 号型规格: 折疊型口罩 颜色: / Colour		1
	Sample ——判定标准:	质量等级: Quality Grade 产品款号或货号: Superscript	ection-No	n-
		powered air-purifying particle respirator 1# 口罩Mask-红色Red; 2# 口罩Mask-深蓝色Dark Blue; 3# 口罩Mask-米黄 4# 口罩Mask-蓝色Blue; 5# 口罩Mask-紫色Purple; 6# 口罩Mask-浮水巴口	色Beige;	A
	检验性质 Test Type	委托检验 样品接收日期 2020-07-23 打造家布日期 Date of Submission Test Submission	- 1980 - 1980 - 1980	07-29
T	检验日期 Test Date 执行标准 est Standards	见附页 See next page(s) 检验结果及符合性见附页。	川章	
	检验结论 Conclusion ————————————————————————————————————	Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit 客户要求过滤效率测试初始过滤效率,并按照GB 2626-2019标准判定。 As per client's request that the Filtration Efficiency is required to test initial filtration efficiency, and judged		
1		according to the standard GB 2626-2019.		

批准: Approver



审核: Checker



编制: Editor

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第2页 共7页

TTTS-WT20214907				*		Page 2 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
1# □罩Mask-红色	≟ Red			.6,	,	
呼吸阻力 Respiratory Resistance	呼气阻力 Expiratory Resistance 吸气阻力 Inspiratory Resistance	Pa Pa	<210 ≤210	未预处理样品 Samples Without Pretreatment: 1: 204 2: 210 预处理样品 Samples With Pretreatment: 1: 174 2: 187 未预处理样品 Samples Without Pretreatment: 1: 206 2: 209 预处理样品 Samples With Pretreatment:	符合 Pass	GB 2626-2019
				1: 179 2: 191		
2# 口罩Mask-深了	蓝色Dark Blue					

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第3页 共7页

<u>T</u>	TTS-WT20214907				<u> </u>		Page 3 of 7
	检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥95. 0	初始过滤效率 Initial Filtration Efficiency: 未预处理样品 Samples Without Pretreatment: 1: 99.67 2: 99.78 3: 99.77 4: 99.72 5: 99.78 6: 99.76 7: 99.75 8: 99.70 9: 99.78 10: 99.76 11: 99.76 12: 99.79 13: 99.74	符合 Pass	GB 2626-2019
					14: 99.73 15: 99.75 预处理样品 Samples With Pretreatment: 1: 98.17 2: 98.41 3: 98.06 4: 97.97 5: 97.76		
	3# 口罩Mask-米責	頁色Beige	Y				V

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第4页 共7页

TTTS-WT20214907				•		Page 4 of 7
检测项目 Test Items	项目描述 Description	単位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	样品表面 Surface of The Sample	/	按标准要求 As per standard requirement	+)	NOMED NO
	部件材料和结构 Component Material and Construction	*	▶ 按标准要求 As per standard requirement	+		\
外观检查 Appearance Inspection	部件经过温度湿度预处理后 The components after the temperature and humidity pretreatment	/	按标准要求 As per standard requirement	+	符合 Pass	GB 2626-2019
	标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		—
4# □罩Mask-蓝1	色Blue		44/	44/		
可燃性 Flammability	续燃时间 Afterflame Time	S	€5	0	符合 Pass	GB 2626-2019
5# □罩Mask-紫1	色Purple	4	,			
头带 Head Harness			呼吸器的每条头 带、带扣及其他 调节部件在承受 10N,持续10s 的拉力时,不应 出现滑脱或断裂 Each head harness, buckle and other adjustment components of the respirator	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019
1			should not have slippage or breaking for 10s under 10N loading	16		16

















天纺标检测认证股份有阻公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验报 Test Report

TTTS-WT20214907						Page 5 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
6# 口罩Mask-深约	录色Dark Green		.6,	.6,		
视野	下方视野 View Blow	0	≥35	61	符合	CD 2200 2000
View	双目视野 Binocular View	%	≥65	>65	Pass	GB 2890-2009

表中"+"表示符合标准要求, "X"表示不符合标准要求。

 $^{^{+}}$ Meet the standard requirements, X Not Meet the standard requirements.



















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验报告 Test Report

第6页 共7页

Page 6 of 7

TTTS-WT20214907























天纺标检测认证股份有限公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tian)

国家针织产品质量监督检验中心

POINTS FOR ATTENTION

第7页 共7页 Page 7 of 7

1.检验报告无"检验专用章"无效。

Report is invalid without stamp of "special seal for the test report".

2.复制报告未重新加盖"检验专用章"无效。

Copy report is invalid without re-stamp of "special seal for the test report".

3.报告无编写、审核、批准人签字无效。

Report is invalid without collective signatures by editor, checker and approver.

4.检验报告涂改无效。

Report is invalid if altered.

5.检验报告或复制报告未加盖骑缝章无效(报告页数多于1页时)。

Report and copy report is invalid without stamp of "Paging Seal" (When the page number more than 1).

6.委托检验仅对来样负责,不承担其他连带责任。

Unless otherwise stated the results shown in this report refer only the sample(s) tested.

7.对于检验结果若有异议,应于收到报告之日起十五日内向本机构提出,逾期不予受理。

Objection should be issued in 15 days upon receiving the report, overdue opinion is inadmissible.

8.未经本机构书面批准,部分复制报告无效。

Part copy report is invalid without the approval of the written documents of the testing organization.

--报告结束 End of report----

注意事项以中文为准The English edition is for reference only

天纺标集团检测单位与地址 Tianfangbiao Groups Others Testing Location

天纺标检测认证股份有限公司

Tianfangbiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津)

China National Clothing Quality Inspection & Supervision Center (Tianjin)

国家针织产品质量监督检验中心

China National Knitted Product Quality Supervision Testing Center

地址:天津市南开区鹊桥路25号

Address: No.25, Quegiao Road, Nankai District, Tianjin, China



扫码下载电子报告



扫码关注天纺标

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验检测报告 Test Report

第1页 共7页 Page 1 of 7

			0
	委托单位/地址 Applicant	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China 惠州博文制造有限公司 送样人 Contact Contact Rimited Contact Contact Contact Rimited Editact Editact	t [/]
i 岁 彖 by Client	生产单位/地址 Manufacturer	思州得文的运行限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo (Guangdong Province, P.R.China	County, Huizhou City,
提供信息		样品名称:防护口罩商标:Sample NameProtective RespiratorTrademark样品总数:50个	KAZE
尸提供信息及要求 Information Drovided by	样品信息 Information of Submitted Sample	Sample Count 50Pieces	
	Sampre	M 単等級: Quality Grade Safety Category 产品款号或货号: 2020-11 Style No. or	
	判定标准: Test	Order No. GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory protection-Non-powered air-purifying particle	respirator
	Standards 样品描述 Sest Part escription	1# 口罩Mask-深灰色(Espresso) 2# 口罩Mask-淺杏色(Light Blush) 3# 口罩Mask-淺灰色(Silver Grey) 4# 口罩Mask-米白色(Champagne) 5# 口罩Mask-杏色 (Natural Sand) 6# 口罩Mask- 黑灰色(Dark Grey) 7# 口罩Mask- 黑色 (Black) 8# 口罩Mask- 黑色十字紋(Black Cross)	NIER
	检验性质 Fest Type	 	市日期 hecking 3020/11-25
-	检验日期 Γest Date	2020-11-19	检测专用章 24 (c)
	执行标准 st Standards	见附页 See next page(s)	
C	检验结论 Conclusion	检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	
	备注 Remarks	客户要求过滤效率测试初始过滤效率,并按GB 2626-2019标准判定。 As per client's request, the initial filtration efficiency is teste for Filtration Efficiency, and judged according to the standard GB 2626-2019.	

批准: Approver



审核: Checker



编制: Editor

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告 Test Report

TTTS-WT20272946

第2页 共7页 Page 2 of 7

_	1115-W12U212946						Page 2 of 1
	检测项目	项目描述	单位	标准值 Standard	实测值	评价 Conclu	执行标准/备注 Test Method/
	Test Items	Description	Unit	Requirement	Results	sions	Remarks
	1# □罩Mask-深2	灰色(Espresso)		6,	.0.		
	可燃性 Flammability	续燃时间 Afterflame Time	s	€5	0	符合 Pass	GB 2626-2019
	2# 口罩Mask-淺衣	ち色(Light Blush)				
	过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥95.0	初始过滤效率 Initial Filtration Efficiency: 未预处理样品 Samples Without Pretreatment: 1: 99.88 2: 99.81 3: 99.83 4: 99.86 5: 99.81 6: 99.91 7: 99.77 8: 99.82 9: 99.87 10: 99.80 11: 99.86 12: 99.87 13: 99.81 14: 99.88 15: 99.87 预处理样品 Samples With Pretreatment: 1: 99.77 2: 99.66 3: 99.56 4: 99.69 5: 99.59	符合 Pass	GB 2626-2019
	3# □罩Mask-淺	灰色(Silver Grey)	1			

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第3页 共7页

						₩3 M 光1 M
TTTS-WT20272946				· · · · · · · · · · · · · · · · · · ·		Page 3 of 7
检测项目	项目描述	单位	标准值	实测值	评价	执行标准/备注
Test Items	Description	Unit	Standard	Results	Conclu	Test Method/
Test Teems	Description	01110	Requirement		sions	Remarks
	呼气阻力 Expiratory Resistance	Pa	≤210	未预处理样品 Samples Without Pretreatment: 1: 159 2: 159 预处理样品 Samples With Pretreatment: 1: 155	•	4NE
呼吸阻力 Respiratory Resistance				2: 121 未预处理样品 Samples Without Pretreatment:	符合 Pass	GB 2626-2019
41	吸气阻力 Inspiratory Resistance	Pa	≤210	1: 163 2: 168 预处理样品 Samples With Pretreatment: 1: 164 2: 137		
4# 口罩Mask-米白	色(Champagne)					
呼吸阻力 Respiratory	呼气阻力 Expiratory Resistance	Pa	≤ 210	未预处理样品 Samples Without Pretreatment: 1: 179 2: 170 预处理样品 Samples With Pretreatment: 1: 161 2: 153	符合	GB 2626-2019
Resistance	吸气阻力 Inspiratory Resistance	Pa	≤210	未预处理样品 Samples Without Pretreatment: 1: 196 2: 193 预处理样品 Samples With Pretreatment: 1: 171 2: 162	Pass	
5# 口罩Mask-杏色	(Natural Sand)				

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告 Test Report

第4页 共7页

TTTS-WT20272946		_				Page 4 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	样品表面 Surface of The Sample	/	按标准要求 As per standard requirement	+ 1	>	N
	部件材料和结构 Component Material and Construction		放标准要求 As per standard requirement	+		1
外观检查 Appearance Inspection	部件经过温度湿度预处理后 The components after the temperature and humidity pretreatment 标识和制造商所提供的各种信息 Label and various information provided by manufacturer		按标准要求 As per standard requirement 按标准要求 As per standard requirement	+	符合 Pass	GB 2626-2019
6# 口罩Mask- 黑	《灰色(Dark Grey)		101	10		
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009
7# 口罩Mask- 黑						
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告 Test Report

第5页 共7页

TTTS-WT20272946				¥		Page 5 of 7
检测项目 Test Items	项目描述 Description	単位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
头带 Head Harness 8# 口罩Mask- 黑	/ 色十字紋(Black (V.	呼吸器的每条头带、带扣及其他调节部件在承受 10N,持续10s 的拉力时,或断入时,或断入时,或断入时,或断处 Each head harness、buckle and other adjustment components of the respirator should not have slippage or breaking for 10s under 10N loading.	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019
可燃性 Flammability	续燃时间 Afterflame A Time	S	≤5	0	符合 Pass	GB 2626-2019

表中"+"为符合标准要求,"×"表示不符合标准要求。

+ Meet the standard requirements, X Not Meet the standard requirements.



TTTS-WT20272946















天纺标检测认证股份有限公司 TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告 Test Report

第6页 共7页

Page 6 of 7

样 밂 Sample





















检验检测报告

Test Report



天纺标检测认证股份有阻公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津)

针织产品质量监督检验中心

(注意事项)

第7页 共7页 Page 7 of 7

1.检验报告无"检验专用章"无效。

Report is invalid without stamp of "special seal for the test report".

2.复制报告未重新加盖"检验专用章"无效。

Copy report is invalid without re-stamp of "special seal for the test report".

3.报告无编写、审核、批准人签字无效。

Report is invalid without collective signatures by editor, checker and approver.

4.检验报告涂改无效。

Report is invalid if altered.

5.检验报告或复制报告未加盖骑缝章无效(报告页数多于1页时)。

Report and copy report is invalid without stamp of "Paging Seal" (When the page number more than 1).

POINTS FOR ATTENTION

6.委托检验仅对来样负责,不承担其他连带责任。

Unless otherwise stated the results shown in this report refer only the sample(s) tested.

7.对于检验结果若有异议,应于收到报告之日起十五日内向本机构提出,逾期不予受理。

Objection should be issued in 15 days upon receiving the report, overdue opinion is inadmissible.

8.未经本机构书面批准,部分复制报告无效。

Part copy report is invalid without the approval of the written documents of the testing organization.

--报告结束 End of report---

注意事项以中文为准The English edition is for reference only

天纺标集团检测单位与地址 Tianfangbiao Groups Others Testing Location

天纺标检测认证股份有限公司

Tianfangbiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津)

China National Clothing Quality Inspection & Supervision Center (Tianjin)

国家针织产品质量监督检验中心

China National Knitted Product Quality Supervision Testing Center

地址:天津市南开区鹊桥路25号

Address: No.25, Quegiao Road, Nankai District, Tianjin, China



扫码下载电子报告



扫码关注天纺标

















国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center






检验检测报告 Test Report

第1页 共5页 Page 1 of 5

				Page I	01 5
		委托单位/地址 Applicant	惠州博文制造有限公司 送样人: Huizhou Bowen Manufacturing Limited Contact 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China		1
	多户 oy Client	生产単位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Guangdong Province, P.R.China	Huizhou Cit	у,
	广提供信息及要求 followation Drovided by	样品信息 Information of Submitted Sample	Final Protective Respirator	4	
	•	Toet	产品款号或货号: 2021-01 Style No. or Order No. GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory protection-Non-powered air-purifying particle respir	ator	4
	T	est Part	1# 口罩Mask-大紅色Racing Red 2# 口罩Mask-深藍色 Royal Blue B# 口罩Mask-橘色 Citrus Orange 4# 口罩Mask-棕色 Maroon 5# 口罩Mask-深緑色Forest Pine 季托检验 样品接收日期 おもない は	股份工	
<u> </u>	Т	它est Type 检验日期 Cest Date 执行标准 st Standards	Commission Test Submission Date of Submission Date		19
		检验结论 onclusion 备注	险验结果及符合性见附页。 Fest results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	1	
J		Remarks			

批准: Approver



审核: Checker

编制: Editor



TTTS-WF21000223















天纺标检测认证股份有阻公司 TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第2页 共5页

Page 2 of 5

TTTS-WF21000223						Page 2 of 5
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu	执行标准/备注 Test Method/ Remarks
1# 口罩Mask-大約	I 紅色Racing Red		Requirement	.6	sions	Remarks
4		4		加载过滤效率: Loading Filtration Efficiency: 未预处理样品 Samples Without Pretreatment: 1: 99.95		1
过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥95. 0	2: 99.97 3: 99.98 4: 99.90 5: 99.94 6: 99.95 7: 99.83 8: 99.80 9: 99.86 10: 99.96 11: 99.89 12: 99.96	符合 Pass	GB 2626-2019
		4	16	13: 99.79 14: 99.81 15: 99.80 预处理样品 Samples With Pretreatment: 1: 99.52 2: 99.59 3: 99.65 4: 99.67 5: 99.61		KNE
2# 口罩Mask-深頭	蓝色 Royal Blue		I	y. 00.01		▼

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第3页 共5页

						朱3贝 共3贝
TTTS-WF21000223				*		Page 3 of 5
检测项目	项目描述	单位	标准值	实测值	评价	执行标准/备注
			Standard		Conclu	Test Method/
Test Items	Description	Unit	Requirement	Results	sions	Remarks
	样品表面 Surface of The Sample	/	按标准要求 As per standard requirement	+1		N
1	部件材料和结构 Component Material and Construction		▶ 按标准要求 As per standard requirement	+		+
外观检查 Appearance Inspection	部件经过温度湿度预处理后 The components after the temperature and humidity pretreatment	/	按标准要求 As per standard requirement	+	符合 Pass	GB 2626-2019
	标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		
3# 口罩Mask-橘色	🔁 Citrus Orange			14/		
	呼气阻力 Expiratory Resistance	Pa	≤210	未预处理样品 Samples Without Pretreatment: 1: 196 2: 193 预处理样品 Samples With Pretreatment: 1: 164		
呼吸阻力 Respiratory Resistance	吸气阻力 Inspiratory Resistance	Pa	<210	1: 164 2: 162 未预处理样品 Samples Without Pretreatment: 1: 200 2: 199 预处理样品 Samples With Pretreatment: 1: 175 2: 170	符合 Pass	GB 2626-2019
4# □罩Mask-棕色	鱼 Maroon					

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告

Test Report

第4页 共5页

TTTS-WF21000223 Page 4 of 5

1113 WI-Z1000ZZ3						rage 4 OI o
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
视野 View	下方视野 View Blow 双目视野	0	≥35	61)符合 Pass	GB 2890-2009
	Binocular View	%	≥65	>65	1 455	
5# 口罩Mask-深終	綠色 Forest Pine					
可燃性 Flammability	续燃时间 Afterflame Time	S	≤5	0	符合 Pass	GB 2626-2019
头带 Head Harness			the respirator should not	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019
1			have slippage or breaking for 10s under 10N loading.	1		1

表中"+"为符合标准要求, "×"表示不符合标准要求。



⁺ Meet the standard requirements, X Not Meet the standard requirements.



TTTS-WF21000223















天纺标检测认证股份有阻公司 TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第5页 共5页

Page 5 of 5



















国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center






检验检测报告 Test Report

第1页 共5页

	1113 1	H 2 1 0 0 2 0 0 7	Page 1 of 5
	委托单位/地址 Applicant	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China 送样人: Contact ### Contac	
岁 s Client	生产単位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Guangdong Province, P.R.China	Huizhou City,
广提供信息及要求 Information Drovided by	样品信息 Information of Submitted Sample	样品名称: 防护口罩 商标: KAZE Sample Name Protective Respirator Trademark 样品总数: 115个 Sample Count 115Pieces 号型规格: FOLD MASK	
	判定标准: Test Standards	GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory protection-Non-powered air-purifying particle respir	ator
	样品描述 Sest Part escription	1# 口罩Mask-藍色 Cobalt Blue 2# 口罩Mask-紫色 Purple Berry 3# 口罩Mask-深緑色 Spearmint 4# 口罩Mask-淺緑色 Key Lime 5# 口罩Mask-粉紅色 Bubblegum 6# 口罩Mask-黑色 Onyx 7# 口罩Mask-白色 Ivory	股份
	检验性质 Test Type 检验日期	委托检验 Commission Test Date of Submission 2021-04-20 2021-04-20 2021-04-20 2021-04-20 2021-04-20	
Te	Test Date 执行标准 sst Standards 检验结论 Conclusion	DMTD NMTD See next page(s) 检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	
	备注 Remarks	/ Composition of the control of the	

批准: Approver



审核: Checker

编制: Editor

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第2页 共5页

TTTS-FH21002007

Page 2 of 5

TTTS-FH21002007						Page 2 of 5
检测项目 Test Items	项目描述 Description	単位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
1# 口罩Mask-藍色	色 Cobalt Blue				•	
1	样品表面 Surface of The Sample	1	按标准要求 As per standard requirement			1
	部件材料和结构 Component Material and Construction	/	按标准要求 As per standard requirement	+		
外观检查 Appearance Inspection	部件经过温度湿度预处理后 The components after the temperature and humidity pretreatment		按标准要求 As per standard requirement		符合 Pass	GB 2626-2019
	标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		
2# 口罩Mask-紫色	E Purple Berry					

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第3页 共5页

TTTS-FH21002007						Page 3 of 5
检测项目	项目描述	单位	标准值	实测值	评价	执行标准/备注
Test Items	Description	Unit	Standard	Results	Conclu	Test Method/
			Requirement	未预处理样品	sions	Remarks
*		+	1º	Samples Without Pretreatment: 1: 99.76 2: 99.70 3: 99.61 4: 99.68 5: 99.87 6: 99.74		4 TE
过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥95.0	7: 99.65 8: 99.86 9: 99.74 10: 99.73 11: 99.76 12: 99.98 13: 99.95 14: 99.97 15: 99.88 预处理样品 Samples With	符合 Pass	GB 2626-2019
3# 口罩Mask-深約	豪色 Spearmint			Pretreatment: 1: 99.50 2: 99.36 3: 99.44 4: 99.47 5: 99.33		
呼吸阻力 Respiratory	呼气阻力 Expiratory Resistance	Pa	≤210	Samples Without Pretreatment: 1: 113 2: 116 预处理样品 Samples With Pretreatment: 1: 115 2: 117	符合	GB 2626-2019
Resistance	吸气阻力 Inspiratory Resistance	Pa	≤210	未预处理样品 Samples Without Pretreatment: 1: 121 2: 120 预处理样品 Samples With Pretreatment: 1: 122	Pass	
	V /			2: 121		
4# 口罩Mask-淺純	綠色 Key Lime					

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告

Test Report

第4页 共5页

TTTS-FH21002007						Page 4 of 5
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
可燃性 Flammability	续燃时间 Afterflame Time	S	€5	0	符合 Pass	GB 2626-2019
5# 口罩Mask-粉約	紅色 Bubblegum					
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009
6# 口罩Mask-黑色	•	!				
可燃性 Flammability	续燃时间 Afterflame Time	S	€5	0	符合 Pass	GB 2626-2019
7# 口罩Mask-白色	色 Ivory		1	1,7		
头带 Head Harness	/	4 1	呼吸器的每条头带、形和及其他调节部件在承受 10N,持续10s的拉力时,不应出现滑脱或断裂 Each head harness, buckle and other adjustment components of the respirator should not have slippage or breaking for 10s under 10N loading	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019

表中"+"表示符合标准要求,"X"表示不符合标准要求。

+ Meet the standard requirements, X Not Meet the standard requirements.

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第5页 共5页

Page 5 of 5

TTTS-FH21002007























国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验检测报告 Test Report


第1页 共5页 Page 1 of 5

			Page I of 5
	委托单位/地址 Applicant	惠州博文制造有限公司 送样人: Huizhou Bowen Manufacturing Limited Contact 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China	
多 为 Client	生产单位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo Coun- Guangdong Province, P.R.China	ty, Huizhou City,
尸提供信息及要求 Information Drovided by	样品信息 Information of Submitted Sample	样品名称: 防护口罩 商标: KAZ Sample Name Protective Respirator Trademark 样品总数: 100个 Sample Count 100Pieces 号型规格: 折叠型口罩 颜色: / Size or FOLD MASK Colour Specification KAZE-01 安全类别: Safety Category 产品款号或货号: 2021-07 Style No. or Order No.	E
	判定标准: Test Standards	GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory particle respirator(KN95)	rotection-Non-powered
	样品描述 escription 检验性质	1# □罩Mask-绿色花纹- photosynthesis 2# □罩Mask-棕紫色花纹- dreamweaver 3# □罩Mask-蓝色花纹- seaglass 4# □罩Mask-红色花纹- sweet nectar 5# □罩Mask-橙色花纹- bloomington 季托检验 本記録を担対	II Report to the second
	Test Type 检验日期 Test Date 执行标准	Commission Test Date of Submission Test Date of Submission Date of Su	
	st Standards 检验结论 Conclusion	See next page(s) 检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Unit	(e)
	备注 Remarks	/	


批准: Approver



审核: Checker



编制: Editor



















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第2页 共5页

						7727 707
TTTS-FH21002582						Page 2 of 5
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
1# □罩Mask-绿f	色花纹- photosyn	thesis				
4	样品表面 Surface of The Sample	1	按标准要求 As per standard requirement	+		LA
	部件材料和结构 Component Material and Construction	/	按标准要求 As per standard requirement	+		
外观检查 Appearance Inspection	部件经过温度湿 度预处理后 The components after the temperature and humidity pretreatment	1	按标准要求 As per standard requirement		符合 Pass	GB 2626-2019
	标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		
2# 口罩Mask-棕蛉	紫色花纹- dreamwe	eaver			'	

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第3页 共5页

TTTS-FH21002582				*		Page 3 of 5
检测项目	项目描述	单位	标准值 Standard	实测值	评价 Conclu	执行标准/备注 Test Method/
Test Items	Description	Unit	Requirement	Results	sions	Remarks
过滤效率		+	16	未预处理样品 Samples Without Pretreatment 1: 99.98 2: 99.95 3: 99.96 4: 99.98 5: 99.97 6: 99.98 7: 99.96 8: 99.97 9: 99.98		
Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥ 95. 0	10: 99.98 11: 99.97 12: 99.98 13: 99.96 14: 99.97 15: 99.98 预处理样品 Samples With Pretreatment 1: 99.93 2: 99.91 3: 99.92	符合 Pass	GB 2626-2019
21 - TWV - TV	7-14-72- 1	4	10	4: 99.93 5: 99.92		10
3# 口罩Mask-蓝色	色花纹- seaglass		V			
呼吸阻力 Respiratory Resistance	呼气阻力 Expiratory Resistance 吸气阻力 Inspiratory	Pa Pa	≤210 ≤210	未预处理样品 Samples Without Pretreatment 1: 118 2: 129 预处理样品 Samples With Pretreatment 1: 103 2: 108 未预处理样品 Samples Without Pretreatment 1: 141 2: 146	符合 Pass	GB 2626-2019
4# 口罩Mask-红色	Inspiratory Resistance 五花纹- sweet ne	Pa ctar	≤210	预处理样品 Samples With Pretreatment 1: 122 2: 120		

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告

Test Report

第4页 共5页

<u>T</u>	TTS-FH21002582				<u> </u>		Page 4 of 5
	检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	视野 View	下方视野 View Blow 双目视野	0	≥35	61	》符合 Pass	GB 2890-2009
L	view	Binocular View	%	≥65	>65	Tass	
	头带 Head Harness		4	呼吸器的每条头带、带扣及其他调节部件在承受 10N,持续10s 的拉力时,不应 出现滑脱或断裂 Each head harness, buckle and other adjustment components of the respirator should not have slippage or breaking for 10s under 10N loading.	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019
	5# 口罩Mask-橙色	色花纹- blooming	ton		6.		
	可燃性 Flammability	续燃时间 Afterflame Time	s	€5	0	符合 Pass	GB 2626-2019
		"··" += T & A	1= (n == n	·			

表中"+"为符合标准要求, "×"表示不符合标准要求。

⁺ Meet the standard requirements, X Not Meet the standard requirements.

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第5页 共5页

Page 5 of 5

TTTS-FH21002582



















国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center





检验检测报告 Test Report

第1页 共7页 Page 1 of 7

			1 agc	1 01 1
	委托单位/地址 Applicant	惠州博文制造有限公司 送样 Huizhou Bowen Manufacturing Limited Conta 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China	/	1
安 y Client	生产单位/地址 Manufacturer	惠州博文制造有限公司 Huizhou Bowen Manufacturing Limited 广东省惠州市博罗县园洲镇下南村新南一路 Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluc Guangdong Province, P.R.China	o County, Huizhou	City,
尸提供信息及要求 Information Provided by	样品信息 Information of Submitted Sample	Final Protective Respirator	KAZE /	
	判定标准: Test Standards	GB 2626-2019 呼吸防护 自吸过滤式防颗粒物呼吸器 Respiratory protection-Non-powered air-purifying partic	le respirator	1
D	样品描述 Test Part escription 检验性质 Test Type	见第2页 See Page 2 委托检验 样品接收日期	THE PORT	-07-30
	检验日期 Test Date 执行标准	Submission 到 2021-07-24 到 2021 见附页 2021-07-24 To 2021-07-24 <t< td=""><td>-29</td><td></td></t<>	-29	
	est Standards 检验结论 Conclusion 备注	See next page(s) 检验结果及符合性见附页。 Test results and compliance refer to next page(s). 检验单位盖章 Stamp of Inspection Uni	检测专用章 (c)	K
	备注 Remarks	Stamp of Inspection Un:	11	

编制:

Editor

审核:

Checker

批准:

Approver

















天纺标检测认证股份有阻公司

TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中化(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第2页 共7页 Page 2 of 7



















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第3页 共7页

TTTS-FH21002650						Page 2 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	Page 3 of 7 执行标准/备注 Test Method/ Remarks
01# □罩Mask-浅	紫色-Light Purp	le			•	
可燃性 Flammability	续燃时间 Afterflame Time	s	€5	0	符合 Pass	GB 2626-2019
02# 口罩Mask-浅	绿色-Light Gree	n				
呼吸阻力 Respiratory Resistance	呼气阻力 Expiratory Resistance 吸气阻力 Inspiratory Resistance	Pa Pa	<210 <≤210	未预处理样品 Samples Without Pretreatment: 1: 83 2: 95 预处理样品 Samples With Pretreatment: 1: 81 2: 78 未预处理样品 Samples Without Pretreatment: 1: 98 2: 108 预处理样品 Samples With Pretreatment: 1: 98 2: 108 700	符合 Pass	GB 2626-2019
03# 口罩Mask-紫	色- Purple	1				

























国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告

Test Report

第4页 共7页

TTTS-FH21002650						Page 4 of 7
检测项目	项目描述	单位	标准值	实测值	评价	执行标准/备注
Test Items	Description	Unit	Standard	Results	Conclu	Test Method/
TOO T TOMO	Description	OHIU	Requirement		sions	Remarks
过滤效率 Filtration Efficiency (KN95)	氯化钠颗粒物 NaCl Particle	%	≥ 95. 0	未预处理样品 Samples Without Pretreatment: 1: 99.98 2: 99.98 3: 99.97 4: 99.98 5: 99.97 6: 99.98 7: 99.98 7: 99.98 9: 99.98 10: 99.98 11: 99.98 12: 99.97 13: 99.98	符合 Pass	GB 2626-2019
04# □罩Mask-蓝	色-Blue	+		13: 99.98 14: 99.98 15: 99.98 预处理样品 Samples With Pretreatment: 1: 99.95 2: 99.96 3: 99.93 4: 99.95 5: 99.93		45
呼吸阻力 Respiratory Resistance	呼气阻力 Expiratory Resistance 吸气阻力	Pa	€210	未预处理样品 Samples Without Pretreatment: 1: 99 2: 91 预处理样品 Samples With Pretreatment: 1: 94 2: 80 未预处理样品 Samples Without Pretreatment: 1: 114	符合 Pass	GB 2626-2019
05# 口罩Mask-棕	Inspiratory Resistance	Pa	≤210	2: 105 预处理样品 Samples Without Pretreatment: 1: 102 2: 91		

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin) 国家针织产品质量监督检验中心 National Knitted Product Quality Inspection & Supervision Center

检验检测报告 Test Report

第5页 共7页

TTTS-FH21002650				<u> </u>		Page 5 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
	样品表面 Surface of The Sample	/	按标准要求 As per standard requirement	+1	>	16
4	部件材料和结构 Component Material and Construction		按标准要求 As per standard requirement	+		1
外观检查 Appearance Inspection	部件经过温度湿 度预处理后 The components after the temperature and humidity	/	按标准要求 As per standard requirement	+	符合 Pass	GB 2626-2019
	pretreatment 标识和制造商所 提供的各种信息 Label and various information provided by manufacturer	/	按标准要求 As per standard requirement	+		4
06# □罩Mask-黄			16/	10		101
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009
07# 口罩Mask-粉	色-Pink					
视野 View	下方视野 View Blow 双目视野 Binocular View	%	≥35 ≥65	61 >65	符合 Pass	GB 2890-2009
08# 口罩Mask-红			10	10		10
可燃性 Flammability	续燃时间 Afterflame Time	S	€5	0	符合 Pass	GB 2626-2019
09# □罩Mask-浅	蓝色-Light Blue	1		T	-	

















国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第6页 共7页

TTTS-FH21002650				*		Page 6 of 7
检测项目 Test Items	项目描述 Description	单位 Unit	标准值 Standard Requirement	实测值 Results	评价 Conclu sions	执行标准/备注 Test Method/ Remarks
头带 Head Harness			呼吸器的每条头带、带扣及其他调节部件在承受 10N,持续10s 的拉力时,不应出现滑脱或断聚 Each head harness、buckle and other adjustment components of the respirator should not have slippage or breaking for 10s under 10N loading	10N负荷持续10秒,头带未 出现滑脱、断裂 The head harness have no slippage or breaking for 10s under 10N loading	符合 Pass	GB 2626-2019
10# □罩Mask-绿色- Green						
视野 View	下方视野 View Blow 双目视野	ō	≥35	61	符合	GB 2890-2009
view	双日代到 Binocular View	%	≥65	>65	Pass	

表中"+"为符合标准要求,"×"表示不符合标准要求。

⁺ Meet the standard requirements, X Not Meet the standard requirements.



TTTS-FH21002650















天纺标检测认证股份有限公司 TianFangBiao Standardization Certification & Testing Co., Ltd.

国家服装质量监督检验中心(天津) National Clothing Quality Inspection & Supervision Center(Tianjin)

检验检测报告 Test Report

第7页 共7页

Page 7 of 7

样 밂 Sample









Date:24.Nov.2020

Page 1 of 6 No.:JST20201124056M

Material Safety Data Sheet (MSDS)

1 Identification of the substance/mixture and of the company/undertaking

.Product name: KAZE Protective Respirator

.Product Model/Type: KAZE-01

.Relevant identified uses -Main use category: Daily respiratory protection

.Manufacturer/Supplier: Huizhou Bowen Manufacturing Limited

.Address: Xinnan 1st Road, Xianan Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong Province, P.R.China

.Tel: +86-752-5895333 .Fax: +86-752-5895330

.E-Mail: min_liao@midasprinting.com

.Contact: Liao Min

.Emergency Telephone Number: +86-158 1644 7685

2 Hazards identification

.NFPA ratings (scale 0 - 4)



Health = 0; Fire = 1; Reactivity = 0

- .Classification of the substance or mixture
- .Classification according to GHS: Not classified as dangerous goods.
- .Classification according to Regulation (EC) No 1272/2008: The product is not classified according to the CLP regulation.
- .Classification according to Regulation 29 CFR 1910.1200:

The product is not classified according to OSHA Hazard Communication Standard (29 CFR 1910.1200).

- .Labelling according to Regulation (EC) No 1272/2008 and GHS: Not applicable.
- .Hazard pictograms and Signal word: Not applicable.
- **.Emergency Overview:** Irritating vapors to respiratory system and eyes may form when product is processing at high temperatures or burning. Molten or heating material in skin contact can cause severe burns.
- .Potential Acute Health Effects:
- .Eyes: Under normal circumstances products is no eye contact hazard.

Heated or burning product: Vapors or fume formed may be irritating to the eye when product is heating or burning.

.Skin: Normally no known acute effects of this product resulting from skin contact. Avoid physical damage that may result from contact with the steel wire, exposure to any chemical should be kept to a minimum.

Heat melted or burning material: Skin contact can cause serious thermal burns.

.Inhalation: Negligible at room temperature. Irritating vapors or fume can be irritating to the upper respiratory tract. when the product is processing at high temperatures or burning.

.Ingestion: This products is not toxic, and normally the product is not easy to ingested

.Potential Chronic Health Effects:

.CARCINOGENIC EFFECTS: This material is not a carcinogen. Classified NONE by NTP, OSHA and by IARC.



Page 2 of 6
No.:JST20201124056M

.MUTAGENIC AND TERATOGENIC EFFECTS: Not available.

.Other hazards: No information available.

3 Composition/information on ingredients

.Description: Mixture of substances as per client submission listed below with additions.

Components Name	CAS Number	Weight Percent (%)
Colored Non-woven fabrics (PP)	9003-07-0	16%
Melt-blown fabric (PP)	9003-07-0	22%
Hot air cotton		12%
Skin friendly non-woven fabric (PP)	9003-07-0	10%
Ear band (Spandex)		22%
Adjustable elastic strap(PP)	9003-07-0	3%
Nose Bridge (PE)	9002-88-4	007
Nose Bridge (Steel wire)	7439-89-6	8%
Nose foam		7%

4 First aid measures

In general, there is no danger of contact with this product. If necessary according to the following first aid measures

- After inhalation: In general the material is not expected to present an inhalation hazard. If inhaling the combustion smoke, leave the site to the fresh air, keep the respiratory tract open, If dyspnea occurs, seek medical attention with oxygen transfusion.
- .After skin contact: Generally no skin contact hazards, Cool skin rapidly if contacted with molten product.

Obtain medical attention for thermal burn and other physical damage.

- After eye contact: Generally no risk of eye contact, The usual measures is flush eyes with plenty of water for a few minutes, occasionally lifting the upper and lower eyelids.
- .After swallowing: Don not eat anything, If symptoms persist consult doctor.
- .Most important symptoms and effects, both acute and delayed: No specific symptoms known.
- .Indication of any immediate medical attention and special treatment needed: No special treatment required.

5 Fire-fighting measures

- .Suitable Extinguishing Media: Water, CO2, Dry Chemicals, Foam-Fog..
- .Unsuitable extinguishing media: Not available.
- .Special hazards arising from the substance or mixture: Dense smoke emitted when burned without sufficient oxygen.

 Powder or dust dispersed in the air is at risk of combustion and explosion.
- .Hazardous decomposition products in case of fire: Heating or burning will release toxic gases or fumes.
- .Firefighters protective equipment and protection measures: Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents Avoid breathing fire gases or vapors.



Page 3 of 6
Date:24.Nov.2020

No.:JST20201124056M

6 Accidental release measures

- .Personal precautions, protective equipment and emergency procedures: For personal protection, see Section 8.
- .Measures for environmental protection: Do not allow much product to reach sewage system or any water course.
- .Methods and material for containment and cleaning up: This product is solid, Small leak is meaningless, where have scattered on the ground only need to clean up it, Scrap should be reclaimed for recycling. The recycling personnel should take the corresponding personal protection.

7 Handling and storage

- **.Precautions for safe handling:** Handling of product may form nuisance dust. Protect personnel. Pneumatic material handling and processing equipment may generate dust of sufficiently small particle size that. Dust accumulations should be controlled through a comprehensive dust control program that includes, but is not limited to, source capture, inspection and repair of equipment, routine housekeeping and employee training in hazards.
- .Conditions for safe storage, including any incompatibilities: Keep in a cool and dry place. Combustible materials should be stored away from extreme heat. The storage area shall be equipped with fire extinguishing devices.

8 Exposure controls/personal protection

- .Control parameters: Not available.
- .Appropriate engineering controls: Handling of these products need keep good ventilation.
- **Respiratory Protection:** No special respiratory protection is required for use of these products. If respiratory protection is needed, use only protection authorized in the U.S. State or EU Standard.
- .Body Protection: No special protective clothing is required.
- .Protective Gloves: Unnecessary, When need choose rubber gloves or other insulated gloves.
- .Eye Protection: Unnecessary, When necessary wear chemical goggles or face shield.

9 Physical and chemical properties

.General Information					
Form:	Solid				
Color:	Maroon; Forest Pine; Sweet Pea; Rose Quartz; Sandy Beige; Racing Red;				
	Citrus Orange; Fuchsia; Ultraviolet; Royal Blue; Power Blue; Dove Grey.				
Odor:	Odorless				
.Change in condition					
Melting point /Melting range:	Not determined				
Decomposition temperature:	Not determined				
.Density:					
.Relative density:	<1 (Water=1)				
.Vapor density:	Not available				
.Solubility in/Miscibility with	V	•	•		
Water:	Insoluble				
.PH-Value:	Not available				



Page 4 of 6
Date:24.Nov.2020 No.:JST20201124056M

10 Stability and reactivity

.Reactivity and Chemical Stability: Stable under normal temperatures and pressures.

.Possibility of hazardous reactions: Will not occur.

.Conditions to Avoid: Avoid high temperature and fire sourceor and contact with hazardous chemicals.

.Incompatible Materials: No further relevant information available.

.Hazardous decomposition Products: Not applicable.

11 Toxicological information

.Toxicity to Animals:

LD50: Not available. LC50: Not available.

.Chronic Effects on Humans: No further relevant information available.

.Other Toxic Effects on Humans: None

12 Ecological information

.Ecotoxicity: May cause long-term adverse effects in the environment.

.Persistence and degradability: Not easily degradable.

.Bioaccumulative potential: No further relevant information available.

.Mobility in soil: No further relevant information available.

.Other adverse effects: No further relevant information available.

13 Disposal considerations

.Product: Must be disposed of in accordance with applicable Federal, state and local regulations.

.Recommendation: Recycling if possible, not be dispose together with household garbage.

. Uncleaned packaging: Recommendation Disposal must be made according to official regulations.

14 Transport information

.UN Proper Shipping Name: Not applicable.

.UN Number: Not applicable.

.Packing Group: Not applicable.
.Marine Pollutant: Not available.

.marine I onnum. Not available.

.Special Provisions for Transport: Not applicable.

.DOT Classification: Not a DOT controlled material (United States).

.TDG Classification: Not controlled under TDG.

.ADR/RID Classification: Not controlled under ADR.

.IMO/IMDG Classification: Not controlled under IMDG.

.ICAO/IATA Classification: Not controlled under IATA.



Page 5 of 6
Date:24.Nov.2020 No.:JST20201124056M

15 Regulatory information

- .Safety, health and environmental regulations/legislation specific for the substance or mixture
- .TSCA inventory: Most Components are listed as commercial status active on the TSCA. And exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
- .WHMIS: Not controlled under WHMIS.
- .California Prop.65: There are no Proposition 65 chemicals present in this products levels that would require a warning under the California Safe Drinking Water and Toxic Enforcement Act.
- .REACH Regulation List of Substances of very high concern (SVHC): None of the ingredients is listed.
- .Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The contents and format of this MSDS Comprehensive reference with ISO Commission Directive ISO11014:2009, GHS, EU Regulation EC No 1272/2008 (CLP) And OSHA Hazard Communication Standard 29 CFR 1910.1200 (g).

DISCLAIMER OF LIABILITY

The information in this MSDS/SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable.

· Abbreviations and acronyms:

NFPA: U.S. National Fire Protection Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals.

CLP: Classification, labeling and packaging.

NTP: U.S. National Toxicology Program.

OSHA: Occupational safety and health administration.

IARC: International agency for research on cancer.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulations Concerning theInternational Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

TDG: Transportation of Dangerous Goods Program.

DOT: U.S. Department of Transportation.

ACGIH: American Conference of Governmental Industrial Hygienists.

TSCA: Toxic Substances Control Act.

LC50: Lethal concentration, 50 percent.

LD50: Lethal dose, 50 percent.



Page 6 of 6 No.:JST20201124056M Date:24.Nov.2020

Sample photo:



**********The End****************